



INTELLIGENT
ROOFING SOLUTIONS

FiberTite® Roofing Systems

FiberTite Technical Bulletin #2012.004

Seaman Corporation • 1000 Venture Blvd. • Wooster, OH 44691
www.fibertite.com

Issue Date: September 14th, 2012
Issued By: FiberTite Technical Services
Re: FiberTite T-Joint Covers

New FiberTite® T-Joint Covers

2012.004 - Page One of One:

“T”-Joints: T-Joints occur where three overlapping sheets of roofing membrane intersect. Because of the extra thickness of membrane at these locations, these joints may not seal properly due to the “memory” of the membrane.

FiberTite T-Joint Covers are used to seal T-Joints at weld intersections of 3 or more sheets or pieces of FTR membrane. Installation of T-Joint Covers is mandatory on all [FiberTite Membrane Systems](#) greater than nominal 45-mil, Vegetated Roofs, Ballast Roofs or where T-Joints have not been properly sealed to exhibit a minimum 1.5” defined crease along the T-Joint.

FTR T-Joint Covers are manufactured from 60-mil non-reinforced [FiberTite](#) KEE membrane.

- Color: Off White, White, Gray, Thermal Tan
- Packaging: 100 Pieces per Carton
- Size: 4” x 4” with rounded corners

[See FTR Detail FTR-TLAP.](#)

If you have any concerns or questions regarding T-Joints or FTR T-Joint Covers, please feel free to contact [FiberTite Technical Services](#) at: 1-800-927-8578.

FiberTite® is a Registered Trademark of Seaman Corporation