



# ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



## Anaconda Sealtite® Fittings

ANAMET Electrical has a fitting and conduit combination for every application.



FITTING SELECTION GUIDE							
			CONSTRUCTION	HARSH ENVIRONMENT	SHIELDTITE	NMUA (NON-METALLIC) TYPE B	MTC (MACHINE TOOL)
FITTING SERIES	STOCK ITEM Y/N	INSULATED THROAT	EF, EFST, UA, CW	HTUA, HC, HCX, ZHUA, OR, EFL	PVC, ZERO HALOGEN	NMUA.	MTC
<b>STEEL FITTINGS LFMC ZINC-PLATED</b>	Y	Y	IP 66/67	IP 66/67	IP 66/67	NA	IP 65
<b>NPT COMPACT LFMC NICKEL-PLATED BRASS</b>	Y	N	IP 66/67	IP 66/67	IP 66/67	NA	IP 65
<b>ISO METRIC COMPACT LFMC NICKEL-PLATED BRASS</b>	Y	N	IP 66/67	IP 66/67	IP 66/67	NA	IP 65
<b>NPT COMPACT LFMC 316 STAINLESS STEEL</b>	Y	N	IP 66/67	IP 66/67	IP 66/67	NA	IP 65
<b>NPT LFMC 304 STAINLESS STEEL</b>	Y	Y	IP 66/67	IP 66/67	IP 66/67	NA	IP 65
<b>NMUA FITTINGS LFNC TYPE B NYLON 66</b>	Y	NA	NA	NA	NA	IP 66/67	NA

IP 65 - Protected from total dust ingress. Protected from low pressure water jets.  
 IP 66 - Protected from total dust ingress. Protected from high pressure water jets from any direction.  
 IP 67 - Protected from total dust ingress. Protected from immersion to 1 m depth.  
 Zinc-plated fittings provide marginal corrosion resistance. Not to be used in salt or corrosive environments.  
 Nickel-Plated Brass fittings provide better protection against corrosion. Use to prevent galvanic corrosion in neutral pH.  
 316 Stainless Steel fittings are the best corrosion protection. Use in very harsh environments to protect against galvanic and chemical corrosion.



### SAVE TIME AND MONEY

From June 1, 2015 - September 30, 2015. All orders of \$500 or more with \$50 or more in fittings will qualify for freight prepaid. Simply mark all qualifying orders with "FittingPromo".

Contact your Pepco Sales Rep for more information about this product.