



ANAMET Electrical, Inc.
Worldwide Leader in Flexible Conduit Technology



Food Grade Fittings

ANAMET Electrical has a fitting and conduit combination for every application.



Type FG Food Grade conduit NSF Certified to NSF/ANSI 169 for special purpose food equipment or devices.



Applications

Where NSF/ANSI 169 certified components are required

- wash down areas
- special purpose food equipment
- poultry packing facilities
- restaurants
- meat packing facilities
- pharmaceutical applications
- waste water treatment



Certifications
FDA Approved Compound
RoHS WEEE COMPLIANT
NSF Component



Construction

- Constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance
- Flexible thermoplastic PVC jacket formulated for food and beverage applications per FDA CFR 21 and NSF 51 requirements
- Jacket is easily cleaned and does not promote bacteria growth

SAVE TIME AND MONEY

From June 1, 2015 - September 30, 2015. All orders of \$500 or more with \$50 or more in fittings will qualify for freight prepaid. Simply mark all qualifying orders with "FittingPromo".

Contact your Pepco Sales Rep for more information about this product.

Continue on Back



ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



Food Grade Fittings

ANAMET Electrical has a fitting and conduit combination for every application.

Product Specifications

Ordering Information

Electrical Trade Size	Inside Diameter		Outside Diameter		Approx Inside Bend Radius	Approx Weight lbs.	Small Carton		
	Inches		Inches		Inches	PER	NAED		
	mm	MIN.	MAX.	MIN.	MAX.	100 FT.	Feet	PIN	
3/8	12	.485	-.505	.690	-.710	2.0	21	100	35502
1/2	16	.620	-.640	.822	-.840	2.5	25	100	35512
3/4	21	.815	-.835	1.030	1.050	3.0	39	100	35522
1	27	1.030	1.055	1.290	1.315	4.0	51	100	35531
1-1/4	35	1.370	1.395	1.635	1.660	4.5	66	50	35541
1-1/2	41	1.575	1.600	1.865	1.900	5.5	104	50	35551
2	53	2.020	2.045	2.340	2.375	7.0	136	50	35561

Note: 1. Above 2" Available on special order.
2. Other colors available on request.

Typical Specification

Conduit shall be Anaconda SEALTITE® Type FG. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked hot dipped zinc galvanized steel core with PVC outer jacket. Type FG conduit shall be used for applications where incidental food contact is possible. Conduit IP 66/67 rated when installed with approved end connectors.



**STAINLESS STEEL CONNECTORS
AVAILABLE IN 3/8" -1" STRAIGHT AND 90°**

Contact your Pepco Sales Rep for more information about this product.