



ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



Non-Metallic Food Grade Fittings

ANAMET Electrical has a fitting and conduit combination for every application.

Type NMFG

Non-Metallic Food Grade conduit NSF Certified to NSF/ANSI 169 for special purpose food equipment or devices.



Applications

Where NSF/ANSI 169 certified components are required

- wash down areas
- special purpose food equipment
- poultry packing facilities
- restaurants
- meat packing facilities
- pharmaceutical applications
- waste water treatment



Certifications
FDA Approved Compound
RoHS WEEE COMPLIANT
NSF Component



Construction

- One-piece construction of rigid, non-metallic reinforcement embedded in flexible PVC wall for exceptional crush and corrosion resistance
- Flexible thermoplastic PVC jacket formulated for food and beverage applications per FDA CFR 21 and NSF 51 requirements
- Jacket is easily cleaned and does not promote bacteria growth

SAVE TIME AND MONEY

From June 1, 2015 - September 30, 2015. All orders of \$500 or more with \$50 or more in fittings will qualify for freight prepaid. Simply mark all qualifying orders with "FittingPromo".

Contact your Pepco Sales Rep for more information about this product.

Continue
on Back



ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



Non-Metallic Food Grade Fittings

ANAMET Electrical has a fitting and conduit combination for every application.

Product Specifications

Ordering Information

Electrical Trade Size	Inside Diameter		Outside Diameter		Approx Inside Bend Radius	Approx Weight lbs.	Small Carton		
	Inches		Inches				PER 100 FT.	Feet	NAED PIN
	mm	MIN.	MAX.	MIN.	MAX.	Inches			
3/8	12	.484	.504	.690	.710	2.0	11	100	3590120
1/2	16	.622	.640	.822	.840	3.5	15	100	3590160
3/4	21	.820	.840	1.030	1.050	4.5	20	100	3590200
1	27	1.041	1.066	1.290	1.315	6.5	26	100	3590260
1-1/4	35	1.380	1.410	1.635	1.660	8.0	36	50	3590350
1-1/2	41	1.575	1.600	1.865	1.900	9.0	44	50	3590400
2	53	2.020	2.045	2.340	2.375	11.0	66	50	3590500

Typical Specification

Conduit shall be Anaconda SEALTITE® Type NMFG. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of non-metallic PVC material and shall be used for inside, outside and corrosive applications. Conduit IP 66/67 rated when installed with approved Type B connectors. Type NMFG conduit shall be used for applications where incidental food contact is possible.

NON METALLIC CONNECTORS ALSO AVAILABLE



Contact your Pepco Sales Rep for more information about this product.