



## ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



### Steel Sealtite® Fittings

ANAMET Electrical has a fitting and conduit combination for every application.



Anamet Electrical now stocks a full line of fittings manufactured in the USA. These zinc plated steel fittings are ideal for use with ANACONDA SEALTITE®. Stocked in sizes 3/8" through 2". 2-1/2" through 4" available upon request.

### Construction

- Zinc plated steel fitting, has a five-piece construction consisting of a gland nut, sealing ring, high-tensile grounding ferrule, insulated throat, and body
- Corrosion resistant protection from moisture and oils
- IP 66/67 rated when installed with approved conduit and tightened to UL 514B torque specifications
- Approved for both exposed and concealed locations. Rated for temperature ranges -49°F to +221°F (-45°C to + 105°C)
- Suitable for use in hazardous locations per NEC Articles 501 Class I Div. 2, Article 502 Class II Div. 1 & 2, Article 503 Class III Div. 1 & 2

**UL Listed**  
**CSA Certified**



### SAVE TIME AND MONEY

From June 1, 2015 - September 30, 2015. All orders of \$500 or more with \$50 or more in fittings will qualify for freight prepaid. Simply mark all qualifying orders with "FittingPromo".

Contact your Pepco Sales Rep for more information about this product.

Continue  
on Back



## ANAMET Electrical, Inc.

Worldwide Leader in Flexible Conduit Technology



### Steel Sealrite® Fittings

ANAMET Electrical has a fitting and conduit combination for every application.




#### Steel Straight SEALTITE Fittings



Size NPT	Sealrite Size (inch)	Min. Internal Bore	Dimensions in inches				Standard Package	PIN Number	Weight (lbs/100)
			A	B	C	D			
1/2"	3/8"	0.42	1.23	0.59	1.09	-	20	7STR38B	10
1/2"	1/2"	0.53	1.26	0.59	1.19	-	20	7STR50B	13
3/4"	3/4"	0.74	1.32	0.59	1.43	-	20	7STR75B	18
1"	1"	0.94	1.75	0.66	1.75	-	5	7STR100B	32
1-1/4"	1-1/4"	1.27	1.60	0.69	2.16	-	5	7STR125B	44
1-1/2"	1-1/2"	1.48	1.76	0.72	2.38	-	5	7STR150B	66
2"	2"	1.92	1.88	0.72	2.88	-	5	7STR200B	85

#### Steel 45° SEALTITE Fittings



Size NPT	Sealrite Size (inch)	Min. Internal Bore	Dimensions in inches				Standard Package	PIN Number	Weight (lbs/100)
			A	B	C	D			
1/2" *	3/8"	0.42	1.00	0.59	1.09	1.06	10	7STR3845B	21
1/2" *	1/2"	0.53	1.00	0.59	1.19	1.25	10	7STR5045B	23
3/4" *	3/4"	0.74	1.13	0.59	1.25	1.31	10	7STR7545B	32
1" *	1"	0.94	1.32	0.66	1.75	1.38	5	7STR10045B	53
1-1/4" *	1-1/4"	1.27	1.32	0.69	2.16	1.50	5	7STR12545B	69
1-1/2" *	1-1/2"	1.48	1.43	0.72	2.38	1.63	3	7STR15045B	99
2" *	2"	1.92	1.63	0.72	2.88	1.75	1	7STR20045B	152

#### Steel 90° SEALTITE Fittings



Size NPT	Sealrite Size (inch)	Min. Internal Bore	Dimensions in inches				Standard Package	PIN Number	Weight (lbs/100)
			A	B	C	D			
1/2" *	3/8"	0.42	1.13	0.59	1.09	1.25	10	7STR3890B	24
1/2" *	1/2"	0.53	1.13	0.59	1.19	1.44	10	7STR5090B	24
3/4" *	3/4"	0.74	1.50	0.59	1.43	1.56	5	7STR7590B	38
1" *	1"	0.94	1.75	0.66	1.75	1.88	5	7STR10090B	70
1-1/4" *	1-1/4"	1.27	1.88	0.69	2.16	2.00	2	7STR12590B	88
1-1/2" *	1-1/2"	1.48	2.00	0.72	2.38	2.38	1	7STR15090B	125
2" *	2"	1.92	2.25	0.72	2.88	2.75	1	7STR20090B	180

\* Malleable iron body

\*\* 2-1/2" - 4" malleable iron fittings available upon request.

Contact your Pepco Sales Rep for more information about this product.