SEPTEMBER 2018 Featured Product

Crouse-Hinds

Celebrating 50 Years

2018

1968

Champ® Pro PVM high bay LED luminaires LED lighting for industrial areas

Engineered for long life and rugged construction

The Champ Pro PVM LED high bay luminaire is a durable, high lumen and high ambient solution for complex industrial applications. Constructed of heavy duty, die cast aluminum, the PVM delivers up to 85,000 lumens and is built to operate in up to 65°C environments.

Primary applications:

- High bay with mounting heights from 60 to 100+ feet
- Locations requiring continuous and consistent light levels
- Areas requiring frequent on-and-off of lights
- Areas that are difficult to re-lamp or that cause production to be stopped during the lamp maintenance process
- Ordinary clean, light industrial production facilities, packaging facilities and warehouses

Key features & benefits:

- High efficacy: 132 lm/W
- Lifetime L87 at 60,000 hours
- · Precision optics in four different distributions
- Extreme ambient temperature range
 PVM60L: -40°C to +65°C
 - PVM85L: -40°C to +50°C
 PVM85L: -40°C to +50°C
- 3G vibration rating with optional surface
- mount bracket
- Two CCT colors: 4000K and 5000K at 85 CRI



Certifications and compliances:

- cULus wet location
- IP66
- NEMA 4X
- ROHS compliant
- DLC pending

Options:

- Control options include standard fixed output or optional 0-10V dimming
- Universal mounting allows for suspended, pipe or hook mount.
 Optional surface mount bracket available.

Construction:

- Heavy duty, die cast aluminum housing for added durability and thermal control
- Standard black polyester powder coat finish painted after fabrication

Contact your Pepco Sales Rep for more information about this product.