

Giving Shape to Ideas





100 ppm print/copy output – up to 6,000 impressions per hour 2,250,000-Page monthly duty cycle meets high-volume demands 1200 x 1200 dpi resolution with advanced LED technology for smooth halftones and sharp text Standard color dual scanning at up to 180 originals per minute Built-in print controller, flexible scanning to Email, FTP, SMB, HDD, USB and TWAIN scanning Job ticket and page editing from 15" touch-screen display for easy on-board press control Job Centro and Hot Folder capabilities for job management and workflow 9,000-Sheet maximum paper capacity for long unattended runs Media sizes up to 12" x 18" and weights up to 350 gsm, duplex capability up to 300 gsm Reliable air-assisted paper-feeding for worry-free printing All-in-one staple finisher with kits for saddle-stitching, hole-punching and post-insertion Simitri® HD toner with Biomass fuses at lower temperatures Optional bypass tray and output tray

EPEAT Gold-certified

bizhub PRO 1100

MONOCHROME DIGITAL PRODUCTION PRINTER / COPIER / SCANNER

press





press

Description bizhub PRO 1100 T Overview ei

The bizhub PRO 1100 delivers real value to any print production environment — with high-speed 100 ppm B&W output, high paper and toner capacity, standard built-in print controller and compact footprint to save space on your production floor. Dedicated to central in-house printing facilities and external print-for-pay services - this device provides sturdy construction, high performance and numerous inline finishing options teamed up with advanced technology for enhanced B&W print quality. Be more productive with high-performance color scanning capability with dual scanning ADF in combination with the powerful print engine.

System specifications Console Туре Resolution 1,200 x 1,200 dpi / 8-bit 256 **Original type** Sheets, Books, Objects Max. Original size 11" x 17" DIMM: 8 GB / HDD: 1TB Memory capacity Paper size Standard: 12" x 18", 11" x 17", 8.5" x 11", 8.5" x 14", 9" x 11", 8" x 13", 5.5" x 8.5' Custom: 7.17" x 5.5" to 12.76 x 18.23", 8.5" x 11" tab paper Image loss Top edge: Max. 3 mm or less Right / Left / Bottom edge: Max. 2 mm or less Warm-up time 390 sec. or less First copy out time 3.4 sec. or less Copy / print speed 100 ppm (Letter) Copy magnification Fixed same magnification: 1:1 \pm 0.5% or less Scaling up: 1:1.154 / 1.224 / 1.414 / 2.000 Scaling down: 1:0.866 / 0.816 / 0.707 / 0.500 Preset: 3 types Zoom: 25 to 400% (in 0.1% increments) Paper capacity Standard: 1,500 sheets x 2 (80 gsm) Paper weight Standard: 40 to 300 gsm (Limitations to paper types apply) Option: 40 to 350 gsm (Only available for middle tray of PF-709) Multiple copy 1 to 9,999 sheets 208 to 240 V, 60Hz, 16 A, Dedicated line Power requirements Max. Power 3.6 kW or less (Main unit + PF-709 + FS-532) consumption Dimensions Main unit + ADF: 39" x 35.75" x 45.75" Including operation panel: 47.75" x 35.75" x 57.25" $(W) \times (D) \times (H)$ Weight 749.5 lb (Main unit) Space requirements Main unit + FS-532 + LU-411: 103-3/4" x 81-1/4" $(\mathsf{W})\times(\mathsf{D})$

Scanning specifications

Туре	Full-Color Scanner
Scanning speed	Simplex: 90 opm (Color/B&W / Letter @ 400 dpi)
	Duplex: 180 opm
Scanning size	11" x 17"
Scanning resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi
Protocol	TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)
Compatibility	Windows Vista* / 7* / 8* / 8.1*
Interface	Ethernet 10Base-T/100Base-TX/1000Base-T
Output format	PDF, TIFF, Encrypted PDF, XPS, Compact PDF, JPEG
	*Supports 32-bit (x86) or 64-bit (x64) environment

Dual scan document feeder (standard)		
Туре	Single pass simultaneous duplex system	
Original size	11" x 17"	
Paper weight	Simplex 35 to 210 gsm / Duplex 50 to 210 gsm	
Paper capacity (80 gsm)	Max. 150 sheets	
Dimensions (W) \times (D) \times (H)	24-1/4" x 22-3/4" x 5-1/2"	
Weight	Approx. 39.75 lb	

Options

optiono	
AU-205H	Various IC card certification device
IC Card reader	
FS-532 Stapling unit	All-in-One 100-sheet staple finisher / 4,200 sheets max. output
GP-501 Multi (GBC)	8.5" x 11" GBC Multi-puncher (7 optional user replaceable dies)
punching unit	
GP-502	8.5" x 11" In-line GBC ring binding unit
Auto ring binding unit	
LU-411	Up to 4,500 sheets / 8.5" x 11" / 40-300 gsm
Large capacity tray	
LU-412	Up to 4,000 sheets / 8.5" x 11" to 12" x 18" / 40-300 gsm
Large capacity tray	
MB-507	Up to 250 sheets / 5.5" x 8.5" to 12" x 18" / 40-300 gsm
Multi bypass tray	
OT-507 Output tray	Up to 150 sheets / 5.5" x 8.5" to 12" x 18" / 62-300 gsm
PF-709 Air assist	Up to 6,000-sheets total / 5.5" x 8.5" to 12" x 18" / 40-350 gsm
paper feed unit	
PI-502 Post inserter	Cover insertion, post finishing for FS-532
PK-522 Punch kit	2/3-hole punching, autoswitching for FS-532
RH-101 / HD-523	Removable HDD Kit
Hard disk kit	
SD-510	Saddle-stitch/folding kit for FS-532 / 25-sheet booklets
Saddle stitch kit	with Half-fold and Tri-fold
ZU-608 Z-fold unit	Z-fold unit for for FS-532 / 11"x17" prints / 2/3-hole punching

Printer specifications	
Туре	Embedded
CPU	Pentium G3420 3.2 GHz
Memory	2 GB
HDD	1 TB 3.5 inch SATA
Print speed	100 ppm
Print resolution	1,200 x 1,200dpi, 600 x 600dpi
PDL	PCL5e/6, PostScript3 (3020), PDF Ver1.7, TIFF Ver. 6 Emulation, PPML (Ver2.2)
Protocol	TCP/IP (LPR, RAW socket), IPX/SPX (NDS, Bindery), NetBEUI, IPP, AppleTalk, WSD, Bonjour, SMB
Compatibility	PCL: Windows Vista* / 7* / 8* / 8.1* / Windows Server 2008* / 2008 R2 2012 / 2012 R2
	PS: Windows Vista* / 7* / 8* / 8.1* Windows Server 2008* / 2008 R2 2012 / 2012 R2 / Mac OS X: 10.6 / 10.7 / 10.8 / 10.9 / 10.10
Fonts	PCL: 80 fonts / PS: 136 fonts
Interface	10Base-T/100Base-TX/1000Base-T, USB 3.0 host, USB 2.0 device

*Supports 32-bit (x86) or 64-bit (x64) environment.



© 2016 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, bizhub PRESS, PageScope, Simitri, and Giving Shape to Ideas are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks of trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC.

100 Williams Drive, Ramsey, New Jersey 07446



Item #: 1100SS 1/16 - S