

# CORE IC PNEUMATIC FORKLIFT

MODEL NUMBER: 8FGU5-32 • LIFT CAPACITY: 3,000-6,500 LBS.  
ITA CLASS 5 • PNEUMATIC TIRES • PRIMARY OUTDOOR USE  
AISLE WIDTH: 138"-159"

## COMMON APPLICATIONS

- 1 Lumber Yards
- 2 Refuse Systems
- 3 Farm Supplies
- 4 Retail- Building Supplies/  
Home Improvement
- 5 Concrete/Stone



MODEL NUMBER	FUEL SOURCE	LOAD CAPACITY (LBS)	ENGINE HP/RPM NET (SAE-HP)	MAXIMUM TRAVEL SPEED (MPH)	MAXIMUM LIFT SPEED FULL LOAD (FPM)	MAXIMUM GRADEABILITY FULL LOAD (%)	BASIC RIGHT ANGLE STACK (IN)	TURNING RADIUS (IN)	OVERALL DIMENSIONS (IN)		
									LENGTH	WIDTH	HEIGHT
8FGU5	Gas	3,000	51/2570	11.5	131	45	92.1	76	87.8	42.1	81.9
8FDU5	Diesel	3,000	53/2200	11.5	128	45	92.1	76	87.8	42.1	81.9
8FGU8	Gas	3,500	51/2570	11.5	131	45	94.1	78	89	42.1	81.9
8FDU8	Diesel	3,500	53/2200	11.8	128	45	94.1	78	89	43.7	81.9
8FGU20	Gas	4,000	51/2570	10.9	118	41	103.2	84.7	101.4	43.7	83.1
8FDU20	Diesel	4,000	55/2200	11.8	121	41	103.2	84.7	101.4	43.7	83.1
8FGU25	Gas	5,000	51/2570	10.9	118	34	105.9	87.5	103.9	43.7	83.1
8FDU25	Diesel	5,000	55/2200	11.8	121	34	105.9	87.5	103.9	43.7	83.1
8FGU30	Gas	6,000	51/2570	11.2	100	26	111.4	92.5	110	43.7	85.5
8FDU30	Diesel	6,000	55/2200	11.8	98	29	111.4	92.5	110	43.7	85.5
8FGU32	Gas	6,500	59/2570	11.2	100	26	112.4	93.3	110.9	43.7	85.5
8FDU32	Diesel	6,500	55/2200	11.8	98	29	112.4	93.3	110.9	43.7	85.5