



Dependable Gas Analysis Solutions



475 SERIES

CONTINUOUS AMBIENT AIR OR PROCESS NITRIC OXIDE ANALYZER

APPLICATIONS

For continuous analysis of nitric oxide (NO) in ambient air or process gas streams using an electrochemical sensor. PPM ranges available only.

FEATURES

- Ambient range PPM (475A) NO by electrochemical sensor
- Process range PPM (475P) NO by electrochemical sensor
- Bright digital readout
- Microprocessor control with push button calibration
- Easy-to-maintain modular layout
- Sensor is temperature controlled for maximum stability
- Built-in sample pump, flowmeter, and filters
- 4 - 20 mA output

OPTIONS

- Hi/Low gas, low flow, and diagnostic alarms available
- Isolated analog, RS232, RS485, MODBUS®, and Ethernet outputs available
- Sample conditioning systems available
- Cabinet purge system available for use in hazardous areas
- Full automatic calibration with touch screen LCD display
- Cold weather package for operation to -5°F (-20°C)
- Cabinet coolers can be fitted to most models
- High temperature filters and probes

CALIBRATION

- Easily zero checked on ambient air
- Span using a known NO in nitrogen (N₂) calibration gas.



Wall Mount (N4) Enclosure



Wall Mount Enclosure with Purge Kit
for hazardous-rated areas

DESCRIPTION

The Nova 475 Series NO analyzers utilize a reliable, electrochemical specific to PPM NO. In operation, the internal sample pump draws the sample gas through the filter, secondary filter, flow meter, and then on to the sensor/detector. The detector output is digitally linearized and then displayed as PPM NO on the digital meter. The output is also available as an analog or digital signal. A regulator will be supplied for applications that have a pressurized sample.

MODELS

- 475AN4 - A range : 0-100 PPM NO (for ambient air analysis)
- 475PN4 - P range : any range from 0-100 to 0-2,000 PPM (for process analysis)

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

Description

| | |
|------------------------------------|--|
| Method of Detection: | PPM NO by electrochemical sensor |
| Ranges Available: | 475AN4 - A range : 0-100 PPM NO (for ambient air analysis) 475PN4 - P range : any from 0-100 to 0-2,000 PPM NO (for process analysis) |
| Resolution: | 10 PPM |
| Accuracy and Repeatability: | ±2% of full scale |
| Drift: | Less than 2% of full scale per month. |
| Response Time (T-90): | Less than 60 seconds to T-90 |
| Ambient Temperature Range: | 40-122°F (5-50°C). Lower temperatures (-20°C, -5°F) with Cold Weather Package. |
| Linearity: | ±2% of full scale |
| Size and Weight: | Physical data will vary depending on enclosure style and options required |
| Power: | 115VAC 60Hz (220VAC 50Hz available) |
| Output Options: | 4-20ma into 500 ohms non-isolated standard Isolated 4-20mA, RS232, RS485, MODBUS®, Ethernet outputs optional |
| Alarms: | High and/or low alarm contacts available, relay contacts SPDT 5A @ 220VAC rating. Low flow alarm optional |

Modbus® is a Registered Trademark of the Modbus Organization, Inc.

UNIQUE APPLICATIONS

Electrochemical NO sensors may produce a response in the presence of other interfering gases. Consult Nova on your specific application. All Nova analyzers are built using proven technologies and techniques. If this product does not suit your application, please contact Nova at 1-800-295-3771. In many cases, we are able to build an analyzer specific to your needs.



NOVA ANALYTICAL SYSTEMS
A UNIT OF TENOVA GOODFELLOW INC.

IN USA:
1925 Pine Avenue • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937
IN CANADA:
270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248
email: sales@nova-gas.com
websales@nova-gas.com



www.nova-gas.com