

NOVA

Dependable Gas Analysis Solutions



362 SERIES

PORTABLE FLUE GAS ANALYZER FOR OXYGEN, CARBON MONOXIDE, AND NOx

APPLICATIONS

Analysis of oxygen (O₂), carbon monoxide (CO), and oxides of nitrogen (NO_x as NO). For checking combustion efficiency, air infiltration, NO_x emissions, and burner & control performance of furnaces, heaters, and boilers. May be used in commercial, industrial and residential applications.

FEATURES

- Long life electrochemical sensors for each gas
- Rugged design that is easy to operate and maintain
- Fast warm-up and response
- Digital readout meter with backlight
- Rechargeable battery operation
- Built-in sample pump, filter, flow meter, and continuous condensate removal
- Weatherproof (WP) cabinet with clear Lexan cover
- Stainless steel probe with sample hose
- For use on any fuel
- Dual CO range: 0-2000 PPM and 0-4.00% CO
- Rapid CO & NO_x reading recovery on 'overdose'
- Pays for itself in months through fuel savings

OPTIONS

- Recorder outputs of 0-1V or 4-20 mA
- Stack temperature readout (362T)
- Sample pre-cooler
- Suitcase (K) style cabinet available
- NO_x as NO + NO₂
- Detachable/portable data logger

CALIBRATION

- Air for O₂ span, CO zero and NO_x zero
- Analyzed mixture of CO and NO in nitrogen for CO and NO span, and O₂ zero

NOVA ANALYTICAL SYSTEMS

www.nova-gas.com



362WP Weather Proof Enclosure



362K Suitcase Enclosure



Optional
Sample
Precooler

DESCRIPTION

The Nova 362 Series are portable analyzers that can provide a detailed analysis of flue gas composition. They have been designed to be accurate, reliable, and easy to use and maintain. The Model 362 has customer-replaceable sensors, which respond quickly to the O₂, CO, and NO_x present in the flue gas sample. The sensor life expectancy is between 3-4 years.

In operation, a built-in sample pump draws in the flue gas sample through the S.S. probe, 12 ft. sample hose, condensate removal filter, secondary filter, flow meter, and then on to the three sensors. The detected O₂, CO, and NO are displayed on separate LCD digital meters, which have a switchable backlight for use in dark areas. The analyzer can be operated for long periods unattended.

The Nova 362 can also optionally indicate net stack temperature for doing fuel efficiency calculations (362T). The temperature sensor is built into the sampling probe. Efficiency charts for each fuel are provided.

The rechargeable battery provides enough power for about 16 hours of continuous operation and the analyzer can be used while it is being recharged. A red LED indicates when to recharge and a green LED verifies that it is receiving recharging power. The battery recharger is included with the analyzer. The rugged dust-tight and water resistant case is ideal for use in harsh environments.

SPECIFICATIONS

Nova reserves the right to specification changes which may occur with advances in design without prior notice.

Description

Method of Detection:	Customer replaceable electrochemical O ₂ , CO and NO sensor.
Ranges Available:	0-25.0% O ₂ ; 0-2000 PPM and 0-4.00% CO (switch selectable), 0-200 to 0-2000 PPM NO _x (as NO); 0-1800°F (0-1000°C) net stack temp (362T)
Resolution:	0.1 % O ₂ ; 1 PPM on CO and NO _x
Accuracy and Repeatability:	±1-2% of full scale
Drift:	2% of full scale per 8 hours of continuous operation
Response Time (T-90):	10-12 seconds for O ₂ ; 20-30 seconds for CO and NO _x
Ambient Temperature Range:	32° to 105°F (0°-40°C)
Linearity:	±1% of full scale of each gas measured
Size and Weight:	WP style - approx. 18" W x 12" L x 5¼" H @ 13 lbs (45 x 30 x 13 cm @ 6 kg) K style - approx. 10 1/2" W x 14" L x 6" H @ 13 lbs (27 x 35 x 15 cm @ 6 kg)
Power:	AC/DC operation, 115VAC 60Hz for recharging (Other voltages available)
Output Options:	4-20 mA or 0-1 VDC

UNIQUE APPLICATIONS

All Nova analyzers are built using proven technologies and techniques. If this product does not suit your application, please contact Nova at 1-800-295-3771. In many cases, we are able to build an analyzer specific to your needs.



NOVA ANALYTICAL SYSTEMS
A UNIT OF TENOVA GOODFELLOW INC.

IN USA:
1925 Pine Avenue • Niagara Falls, NY • 14301
Tel: 1-800-295-3771 • 716.285.0418 • Fax: 716.282.2937
IN CANADA:
270 Sherman Avenue North • Hamilton, ON • L8L 6N5
Tel: 905.545.2003 • Fax: 905.545.4248
email: sales@nova-gas.com
websales@nova-gas.com



www.nova-gas.com