

PSS 2010

High Performance Pallet Strapping at a Great Price.

The PSS2010 is an excellent choice for large package strapping where it is not necessary to feed strap through a pallet void. Available in several different arch and strap sizes, the PSS2010 is a heavy duty, versatile strapper suitable for a broad range of applications. The proven strapping head produces high tension and consistent, friction welded seal joints for both polyester and polypropylene. The extensive list of standard features on the PSS2010 are listed below. Plus, it's backed by the best warranty in the industry, 99% parts availability within 24 hours, and unlimited, free telephone support for the life of the machine. If you are looking for a reliable pallet strapper that is operator and maintenance friendly, you can't get a better value than the PSS 2010.

Standard features of the PSS 2010 Include:

- **Electronic Tension Control**
Tension is adjusted by simply turning a dial.
- **Siemens PLC Control Unit**
Reliable Siemens PLC reduces adjustments and maintenance
- **Reliable Friction Welding System**
Welds on both PET and PPY are reliable and consistent
- **Auto Strap Ejector and Re-feed**
Missed straps are ejected and the PSS 2010 returns to the ready position
- **Acceptable for both Polypropylene and Polyester**

Options available on the PSS2010:

- Can be automated with conveyors
- Heavy duty foot pedal
- Available with power or gravity conveyors
- Available with a 8" (200mm) or 9" (280mm) I.D. core, 16" (406mm) standard



PSS2010 WITH A 55X65 ARCH

Available Arch Sizes

Arch Sizes - PSS2010

Width: In/mm 23.6/600 31.5/800 39.4/1000 47.2/1200 55.1/1400

Height: In/mm

| | | | | | |
|-----------|---|--|--|--|--|
| 33.4/850 | | | | | |
| 41.3/1050 | | | | | |
| 49.2/1250 | | | | | |
| 57.1/1450 | S | | | | |
| 65/1650 | | | | | |
| 72.8/1850 | | | | | |
| 80.7/2050 | | | | | |
| 88.6/2250 | | | | | |
| 96.4/2450 | | | | | |