

PURCLEAN™ SPOT FREE RINSE SYSTEM

1,000GPD Spot Free Rinse System

Features:

- Water Stabilizer (replaces softener)
- Inlet & Pressure Pump
- Carbon Tank with Auto Back Flushing Head
- Multi-Stage Pressure Pump
- Low Pressure Shut Off
- Automatic Membrane Flush
- Production & Reject Meters
- On Board TDS Meter
- Aluminum Frame
- Repressurization and / or Reject Recapture Pump
- Thin Film Membrane
- Hinged Control Box - Quick and Easy Internal Access
- ETL Listed



Specifications

Water Requirements	(2) 1" Water line w/FPT ball valves, 20GPM at 30PSI. Mount 4 feet up from floor to the right of the spot free rinse system and (1) drain.		
Electrical Requirements	1Ph	(1) 220V 20 Amp single phase circuit with its own L6-20 locking receptacle. Put plug 5 feet up from the floor to the right of the spot free rinse system.	
	3Ph	(1) 208/230 or 460/480 20 amp circuit, put circuit 5 feet up from the floor to the right of the spot-free rinse system.	
RO Output	Production - .7 GPM		
Reject	.8 GPM		
RO Motor	1HP Booster pump		
RO Motor Amps	1Ph 208/230 = 10.25 amps	3Ph 208/230 = 5.5 amps	3Ph 460/480 = 3.25 amps
Dimensions	30" wide x 36" tall x 12" deep		
Net Weight	300 lbs.		