

## PURCLEAN™ SPOT FREE RINSE SYSTEM

### 3,000GPD Spot Free Rinse System

#### Features:

- Water Stabilizer (replaces softener)
- Inlet & Pressure Pump
- Carbon Tank with Auto Back Flushing Head
- Multi-Stage Pressure Pump
- Low Pressure Shut Off
- Automatic Membrane Flush
- Production & Reject Meters
- On Board TDS Meter
- Aluminum Frame
- Repressurization and / or Reject Recapture Pump
- Thin Film Membrane
- Hinged Control Box - Quick and Easy Internal Access
- ETL Listed



#### Specifications

<b>Water Requirements</b>	(2) 1" Water line w/FPT ball valves, 20GPM at 30PSI. Mount 4 feet up from floor to the right of the spot free rinse system and (1) drain.		
<b>Electrical Requirements</b>	1Ph	(1) 220V 20 Amp single phase circuit with its own L6-20 locking receptacle. Put plug 5 feet up from the floor to the right of the spot free rinse system.	
	3Ph	(1) 208/230 or 460/480 20 amp circuit, put circuit 5 feet up from the floor to the right of the spot-free rinse system.	
<b>RO Output</b>	Production - 2.1 GPM		
<b>Reject</b>	2.2 GPM		
<b>RO Motor</b>	1.5HP Booster pump		
<b>RO Motor Amps</b>	1Ph 208/230 = 11.5 amps	3Ph 208/230 = 6.7 amps	3Ph 460/480 = 3.85 amps
<b>Dimensions</b>	30" wide x 44" tall x 12" deep		
<b>Net Weight</b>	500 lbs.		
<b>Delivery Pump</b>	Standard delivery pump 15 GPM max at 50 PSI max. Automatic freshwater bypass pressure and GPM varies depending on which car wash application (call PurClean for more info).		