

LMR BATTERY SPECIFICATIONS	PART NUMBER
	WVX-KNB40LIS

COMPATIBLE RADIOS	Kenwood NX220, NX320, NX420, NX3200, NX3220, NX3300, NX3320, TK2140, TK2160, TK2170, TK2360, TK3140, TK3160, TK3170, TK3173, TK3360
REPLACES OEM BATTERY	KNB-40LCV, KNB-68LC
HAZ LOC RATINGS	Certified by SGS to TIA-4950 / CSA C22.2 No. 157 / UL 913 5th Edition standard for intrinsically safe use (Class I, II, III / Division 1 / Groups C-G / -20° C to 40° C, T3C) and non-incendive use (Class I, II, III / Division 2 / Groups A-G / -20° C to 40° C, T3C).
INGRESS PROTECTION	IP64 rated
COMPATIBLE CHARGERS	Endura TWC1-KW3, TWC1M-KW3, TWC2M-KW3-D, TWC6M-KW3, TWC12M-KW3-D / Logic LEVCA-KW3
CONDITIONER COMPATIBLE	N/A
VOLTAGE / CAPACITY	7.4V / 1900 mAh
CHEMISTRY	Li-Ion
CELL TYPE	Panasonic NCA103450 (Japanese)
OPERATING TEMPERATURE	-20° C to +40° C (discharge, T3C) / 10° C to +45° C (charge)
CHARGE CYCLES	>500
CHARGE TYPE	Rapid
PROTECTION TYPES	Over charge / over discharge / over temperature
HOUSING MATERIAL / SEAL	ABS / ultrasonic weld
METAL WELDING	Pure nickel tabs w/ spot welder
CLIP	N/A
WARRANTY	12 months
PRODUCT PHOTO (Brand: Logic Energy)	