- endlessly clever

A well proven continuous liner with static dissipative properties.

Tested and approved for food and pharma contact.

- Complies with FDA 21 CFR
- Fully compliant to 2002/72/EC and amendments
- Meets test parameters of EP 3.1.3
- No animal derived components (BSE/TSE)
- REACH compliant and SVHC free
- Multilayer technology (PE)



A well proven continuous liner with static dissipative properties



Paxxo was founded in 1980 based on patented technology of making continuous liners called Longopac. Paxxo has in house extrusion and folding and is the leading manufacturer of continuous liners. The complete production process is made in Sweden with a fully automated production line and to the highest quality standards. Longopac is used in a wide range of industries and applications which has generated substantial volume advantages and a low cost per meter.

The Longopac bagging system is ideal as a continuous liner system for offloading powders from vessels to drums. Using Longopac as your continuous liner eliminates cross contamination of powders, improves the working environment and protects the staff and product. The system can be integrated in isolators or safety cabinets for safe and efficient handling of waste or products.



We offer the Longopac cassette in 3 different formats, Maxi, Midi and Mini. The length depends on the thickness of the film.

	Dart drop*	Length	Thickness	Diameter	ESD
MAXI STANDARD	. 510g	110m	. 25my	570	.1.0E +10 Ohm
MAXI STRONG	. 700g	80m	. 33my	570	.1.0E +10 Ohm
MIDI STANDARD	. 450g	85m	. 22my	465	.1.0E +10 Ohm
MIDI STRONG	. 680g	70m	. 30my	465	.1.0E +10 Ohm
MINI STANDARD	. 350g	60m	. 18my	360	.1.0E +10 Ohm
MINI STRONG	. 470g	45m	. 26my	360	.1.0E +10 Ohm

*Dart drop is measured according to ASTM D-1709 The value is an average measured end of shelf life.

easi) recycling



This is a well proven continuous liner with static dissipative properties. It is tested and approved for food and pharma contact.

- Complies with FDA 21 CFR
- Fully compliant to 2002/72/EC and amendments
- Meets test parameters of EP 3.1.3
- 5-year shelf life
- Available with guaranteed level of antistat or standard
- Available with gamma sterilization
- No animal derived components (BSE/TSE)
- REACH compliant and SVHC free
- Multilayer technology (PE)

CHEMICAL	RESISTANCE	
Acetone	Fair	
Acetonitrile	Excellent	
Butyl Acetate	Excellent	
Cyclohexane	Fair	
Cyclohexane/Ethylacetate 50:50	Good	
Diethylether	Good	
Dimethylformamide	Excellent	
Ethanol	Excellent	
Ethylacetate	Excellent	
HCL 37%	Excellent	
n-Heptane	Good	
HMDS	Excellent	
Isopropanol	Excellent	
KOH 50%	Excellent	
Methanol	Excellent	
2-Methoxyethanol	Excellent	
Methylethylketone	Excellent	
n-Methylpyrrolidone	Excellent	
Methyl-tert-buthylether	Excellent	
Mineral oil	Excellent	
Reagent (3A) Alcohol	Excellent	
NaOH 50%	Excellent	
Tetrahydrofuran	Fair	
Toluene	Good	
Water destilled	Excellent	



Easi Recycling NZ Limited.

Unit 2B, 3 Northside Drive, Whenuapai, Auckland 0814 Freephone: 0800 342 3177 Email: info@easirecycling.co.nz

www.easirecycling.co.nz