



**NOTES & SPECIFICATIONS:**

1. ProTek Pipe Shoes are made from crosslinked high density vinyl ester resin
2. The ProTek Pipe Shoe shall be secured to pipe with 3/4" S.S. banding straps and banding clips
3. The ProTek Pipe Shoe shall be sealed to the pipe with a Silicone sealing bead.
4. Temperature range is -320° F (-196° C) to +400° F (+204° C).

ITEM	QTY	DESCRIPTION	MATERIAL
1	1	Pipe Shoe	Crosslink High Density Vinyl Ester
2	1	IS800 Series Silicone	Silicone Adhesive Sealant
3	2	3/4" S.S. Banding Straps	Stainless Steel
4	2	3/4" Banding Clip	Stainless Steel

CUSTOMER: DATE: CD NAME: CONTACT: TEL NO: E-MAIL: RFQ: PQ: REF:	DWN.	DATE	03/18/2015		
	CHK.				
	ENG.				
	MFG.	APP			
	APPR.				
			<b>ADVANCED PIPING PRODUCTS</b> 5611 Guhn Road Suite A1, Houston, TX 77040 Tel. 713-956-2922 Fax 713-956-4090 www.appinc.co		
			DWG DESCRIPTION ProTek Pipe Shoe		
		SIZE	A	PPS0315	REV. 0
NEXT ASSY		QTY	SCALE	None	SHEET 1 OF 1