



NPS (in.)	W (in.)	A (in.)	F (in.)	L (in.)	T (in.)
0.75	1.5	5.5	2	12	3/8
1	1.5	5.5	2	12	3/8
1.5	1.5	5.5	2	12	3/8
2	1.5	5.5	2	12	3/8
2.5	1.5	5.5	2	12	3/8
3	3.5	6.5	1.5	18	3/8
4	3.5	6.5	1.5	18	3/8
6	5	8	1.5	18	1/2
8	5	8	1.5	18	1/2
10	10	13	1.5	18	1/2
12	10	13	1.5	18	5/8
14	10	13	1.5	24	5/8
16	14	17	1.5	24	5/8
18	14	17	1.5	24	5/8
20	14	17	1.5	24	5/8
24	20	23	1.5	24	5/8
26	20	23	1.5	30	3/4
28	20	23	1.5	30	3/4
30	24	27	1.5	30	3/4
32	24	27	1.5	30	3/4
34	24	27	1.5	30	3/4
36	24	27	1.5	30	3/4
38	30	33	1.5	30	3/4
40	30	33	1.5	30	3/4
42	30	33	1.5	30	3/4
44	30	33	1.5	30	3/4
48	39	42	1.5	30	3/4
52	39	42	1.5	30	3/4
54	43	46	1.5	30	3/4
56	43	46	1.5	30	3/4
60	43	46	1.5	30	3/4
66	50	53	1.5	30	3/4
72	54	57	1.5	30	3/4

Notes & Specifications:

- Internal chambers to be filled with EPS foam blocks by APP
- Insulated pipe shoe shall be secured to pipe with 3/4" S.S. banding straps and 3/4" banding clips
- Insulated pipe shoe shall be secured to the pipe with APP Epoxy
- Minimum operating temperature of -320°F (-198°C)

ITEM	DESCRIPTION	MATERIAL
1	CryoTek Pipe Shoe	CryoTek IPN Composite
2	Internal Insulation Blocks	EPS Foam
3	3/4" Banding	Stainless Steel
4	3/4" Banding Clip (for use with Banding)	Stainless Steel

CUSTOMER:
 DATE:
 Project:
 CONTACT:
 TEL. NO.
 E-MAIL:
 RFQ:
 PO:
 REF:

DWN. MC DATE 9/22/15
 CHK.
 ENG.
 APPR.
 MFG. APP
 SO.
 NEXT ASSY QTY

ADVANCED PIPING PRODUCTS
 5611 Guhn Road Houston TX, 77040
 Tel. 713-956-2922 Fax 713-956-4090
 www.appinc.co

DWG DESCRIPTION
 CryoTek Pipe Shoe

SIZE A CTPS REV. 0
 SCALE None SHEET 1 OF 1