

# Ultra-Wideband Dual Port Vehicular Antenna WBC2600M

The WBC2600M is a robust ultra-wideband dual port antenna effectively covering the VHF, UHF and SHF bands. It is well suited for high power ECM and tactical communication applications, especially where a multiple antenna set-up is not possible, or antenna co-location problems may occur.

- Two antennas integrated in the same mechanics, combining the advantage of a low visual signature with the capability for an extended frequency range
- High band, ground plane independent antenna positioned at the top for optimum coverage
- High power rating, more than 300 W in total



Product details*	
Frequency range	Port 1: 20 – 512 MHz Port 2: 500 – 6000 MHz
Polarization	Nominally vertical
Radiation pattern	Omnidirectional
Gain	Measured patterns on request
VSWR	Port 1: ≤ 3.5 / Port 2: < 3.5
Nominal Impedance	50 Ω
Power rating (RMS)	Port 1: 140 W Port 2: 500-1000 MHz: 200 W 1000-2000 MHz: 150 W 2000-4000 MHz: 100 W 4000-6000 MHz: 80 W
Standard color	Black
Radiator	Aluminium enclosed in fibreglass radome with rubber coated shock absorption spring
Height	1730 mm
Weight	6.1 kg

Installation*	
RF connection	Two Female N-type connectors
Mounting	4-hole US pattern mount

\*Specific adjustments on request

Order number	
WBC2600M	Antenna as described above
WBC2600M-R1	Antenna with removable radiator (weight: 7.1 kg)