



Load King Stinger 10-47 10 Ton Boom 2020 Freightliner M2106

CRANE SPECIFICATIONS

Engine

Cummins B6.7 300HP
2) DTNA Batteries
18.7 CFM Air Compressor

Transmission

Allison 2500 RDS
Automatic Transmission
With PTO Provision

Front Axle

Detroit DA-F-13.3-3 13,300#
FF1 71.5 KPI/3.74 Drop
Single Front Axle
Tires: 11R22.5
Steel Wheels

Front Suspension

12,000# Mono Taperleaf Front Suspension

Rear Axle

Detroit DA-RS-21.0-4 21,000#
R-Series Single Rear Axle
(1) Driver Controlled Differential Lock
Ratio 5.22
Tires: 11R22.5
Steel Wheels

Rear Suspension

21,000# 52 Inch Variable Rate Multi-Leaf
Spring Rear Suspension With Leaf Spring
Helper

Fuel Tanks

50 Gallon Aluminum Fuel Tank - RH
50 Gallon Aluminum Fuel Tank - LH
6 Gallon DEF Tank

Cab Features

106 Inch BBC Flat Roof Aluminum Conventional
Cab
Air Cab Mounting
Fiberglass Hood
Single 14 Inch Round Hadley Air Horn Under LH
Deck
Dual Electric Horns
Door Locks And Ignition Switch Keyed The Same
(5) Amber Marker Lights
Dual West Coast Molded-In Color Heated Mirrors
LH And RH 8 Inch Molded-In Color Convex
Mirrors
Opal Gray Vinyl Interior
LH And RH Electric Door Locks
Basic High Back Air Suspension Driver Seat With
Mechanical Lumbar And Integrated Cushion
Extension
2 Man Tool Box Mid Back Non Suspension
Passenger Seat
Dual Driver Seat Armrests, No Passenger Seat
Armrests
LH And RH Integral Door Panel Armrests
Gray Mordura Cloth Driver Seat Cover
Gray Mordura Cloth Passenger Seat Cover
Adjustable Tilt And Telescoping Steering Column
Woodgrain Driver Instrument Panel
Woodgrain Center Instrument Panel

Load King 10-47 10 Ton Boom

10 Tons Capacity Rating.
MainFrame Consists Of All Steel Box Construction
Subframe Length Designed For 16' Flatbed.
Dual Side Stand-Up Controls With Foot Throttle Pedal
Rotation Planetary Gearbox Hydraulic Motor Driven With 370-Degrees
Of Non-Continuous Swing Rotation
Crane Consoles Include 4 Lever Crane Function Control Handles
4 Lever Outrigger Control Handles
Warning Light For High Hydraulic Oil Temperature
Standard Two-Speed Planetary Hoist - hydraulic motor driven - Maximum
Line Pull 7,900lbs / 3,600lbs @ Low Speed/High Speed Combined Flow Switch
Rated Capacity Limiter System With Digital Read Out Display, And
Integrated Work Area Definition Program
47' Three Section Keel Designed Boom Full Power, Mechanically
Synchronized
210' x 1/2" Rotation Resistant Cable
Load Ball With Non-Swivel Hook
16' Steel Flatbed
Removeable Boom Rest
180 Degree Capacity Only Without Front Bumper Outrigger
Hot Shift PTO

855-399-5991 -- www.loadkingmfg.com

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

- PRICE: \$167,900
- FET Not Applicable
- Ex Works: Kansas City, MO

QUOTE NUMBER: HC1.10-D_19

EXPIRATION DATE: 6-30-19