



# Load King Stinger 19-70 19 Ton Boom 2020 Freightliner M2106

## CRANE SPECIFICATIONS

### Engine

Cummins B6.7 300HP  
2) DTNA Batteries  
18.7 CFM Air Compressor

### Transmission

Allison 2500 RDS  
Automatic Transmission  
With PTO Provision

### Front Axle

Detroit DA-F-13.3-3 13,300#  
FF1 71.5 KPI/3.74 Drop  
Single Front Axle  
Tires: 11R22.5  
Steel Wheels

### Front Suspension

12,000# Mono Taperleaf Front Suspension

### Rear Axle

Detroit DA-RS-21.0-4 21,000#  
R-Series Single Rear Axle  
(1) Driver Controlled Differential Lock  
Ratio 5.22  
Tires: 11R22.5  
Steel Wheels

### Rear Suspension

21,000# 52 Inch Variable Rate Multi-Leaf  
Spring Rear Suspension With Leaf Spring  
Helper

### Fuel Tanks

50 Gallon Aluminum Fuel Tank - RH  
50 Gallon Aluminum Fuel Tank - LH  
6 Gallon DEF Tank

### Cab Features

106 Inch BBC Flat Roof Aluminum Conventional  
Cab  
Air Cab Mounting  
Fiberglass Hood  
Single 14 Inch Round Hadley Air Horn Under LH  
Deck  
Dual Electric Horns  
Door Locks And Ignition Switch Keyed The Same  
(5) Amber Marker Lights  
Dual West Coast Molded-In Color Heated Mirrors  
LH And RH 8 Inch Molded-In Color Convex  
Mirrors  
Opal Gray Vinyl Interior  
LH And RH Electric Door Locks  
Basic High Back Air Suspension Driver Seat With  
Mechanical Lumbar And Integrated Cushion  
Extension  
2 Man Tool Box Mid Back Non Suspension  
Passenger Seat  
Dual Driver Seat Armrests, No Passenger Seat  
Armrests  
LH And RH Integral Door Panel Armrests  
Gray Mordura Cloth Driver Seat Cover  
Gray Mordura Cloth Passenger Seat Cover  
Adjustable Tilt And Telescoping Steering Column  
Woodgrain Driver Instrument Panel  
Woodgrain Center Instrument Panel

### Load King 19-70 19 Ton Boom

19 Tons Capacity Rating  
Mainframe Consists Of All-Steel, Box Construction  
Subframe Length Designed For 20' Flatbed  
Dual Side Stand-Up Controls With Foot Throttle Pedal  
Rotation Planetary Gearbox - Hydraulic Motor Driven With  
370-Degrees Of Non-Continuous Swing Rotation  
Crane Consoles Include 4 Lever Rubber Booted Control Handles  
Rated Capacity Limiter System With Digital Read Out Display, And  
Integrated Work Area Definition Program  
Boom Tip Head Is Equipped With 2 Bottom Head Sheaves  
High Capacity Full Flow Oil Filtration System With A 70 Gallon Capacity  
Standard Two-Speed Planetary Hoist - Hydraulic Motor Driven - Maximum  
Line Pull 11,854Lbs / 5,532Lbs @ Low Speed/High Speed Combined Flow  
Switch  
Warning Light For High Hydraulic Oil Temperature  
70' Three Section Keel Designed Boom, Full Power, Mechanically  
Synchronized  
24'-40' (Two Piece) Jib  
240' X 9/16" Rotation Resistant Cable  
Load Ball With Non-Swivel Hook  
20' Steel Flatbed  
Single Front Bumper Outrigger (360 Degree Capacity)  
Hot Shift PTO

855-399-5991 -- [www.loadkingmfg.com](http://www.loadkingmfg.com)

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.  
Pictures are representative and may not be identical.

- PRICE: \$201,900
- FET Not Applicable
- Ex Works: Kansas City, MO

QUOTE NUMBER: HC2.10-D\_19

EXPIRATION DATE: 6-30-19