



Load King Stinger 80-126 80 Ton Boom New Kenworth T800

CRANE SPECIFICATIONS

Engine

X15 505Hp
4 Paccar Batteries
18.7 CFM Air Compressor
120V Block Heater
Intebrake

Transmission

Allison 4700RDS 7-speed

Front Axle

Twin Steer Front Axle
40,000 lbs. Dana Spicer
Tires 425/65R22.5
Aluminum Wheels

Front Suspension

Taper Leaf Springs
Shocks 40,000 Lb

Rear Axle

Tridem Dana Spicer T69-170HP
Differential Lock
Tires 455/55R22.5
Aluminum Wheels
Ratio 4.78

Rear Suspension

Tridem Neway ADZ369 69K
54 Inch Axle Spacing

Fuel Tanks

100 Gallon Aluminum Fuel Tank
11 Gallon DEF Tank

Cab Features

Stainless Steel Aluminum Bumper
Front Tow Hooks
Sloped Metton hood With Split Fenders
Adjustable Telescoping Tilt Steering Column
Splendor Cab Interior
Kenworth Driver Seat Air Suspension
With Single Chamber Air Lumbar Support
Kenworth Toolbox Plus Passenger Seat
Manual LH & Electric-Powered RH Door Window
Electric LH & RH Door Locks
Dual Convex Heated Mirror 8.5 Inch
Dual Moto Heated Mirrors 7 In. X 16 In.
(5) Marker Lights rectangular LED
Deluxe A/C And Flameless Hydraulic Heater

Optional

2- Axle Boom Dolly Add: \$35,000

Load King 80-126 80 Ton Boom

80 Ton Capacity Rating
Mainframe Consists Of All-Steel Formed Construction
X Pattern Hydraulic Swing Out And Telescopic 3 Position
4 Outrigger Beam System
Outrigger Control Station In The Crane Cab
Continuous Rotation Foot Peddle Swing Brake And 360 Degree Swing Lock
Hydraulic Oil cooler
Premium Contoured Flexible Fenders
Aluminum Diamond Plate Decking
Access Ladders And Steps
Recessed Locking Storage Box In Decking
126' Four Section Full Power Mechanically Synchronized Boom With
Welded Boom Dolly Lugs
Operators Cab Hydraulically Tilting Fully Adjustable From 0 To 18 Degrees
With 6-Way Adjustable Heated Seat
Joystick Controls In Armrests Are Adjustable Fore And AFT, Pivot Up 90° With
Shutoff Controls
360-Degree House Lock
Rated Capacity Limiter System With Digital Read Out Display With
Integrated Work Area Definition Program
12,000 Lbs Removeable Counterweight Package
33'-57' (2 Piece) Offsetting Jib
Single Main Planetary 2Spd Hoist -489 FPM (149 M/Min)
Maximum Line Speed 18,450 Lb. (8369 Kg) Maximum Line Pull
Integral Automatic Brake
Electronic Drum Rotation Pulse Indicators In Control Handles
Standard Upper Counterweight With (Optional) Auxiliary Hoist 3,000Lbs,
Auxiliary Winch Package With Single Sheave Extension
600' x 3/4" Rotation Resistant Cable (Both Winches)
12 Ton Load Ball With Hook
5-Sheave (80 Ton) Load Block
Hot Shift PTO
(2) Remote Outrigger Control Stations Located Each Side Of Unit
Boom Dolly Prep Package

855-399-5991 -- www.loadkingmfg.com

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

- PRICE: \$809,918
- FET Not Applicable
- Ex Works: Kansas City, MO

QUOTE NUMBER: HC3.11-D_19

EXPIRATION DATE: 6-30-19