



# Load King 60-110TC 60Ton Boom

## CRANE SPECIFICATIONS

### Engine

Detroit Diesel DD13 450HP  
6-Cylinder  
Intercooled Turbo Charger

### Transmission

Eaton 11 Speed  
Ultra Shift Transmission

### Fuel Tanks

100 Gallon Fuel Tank

### Carrier

8X4 Drive  
Box Type Chassis Construction  
Full Aluminum Decking  
Hydraulic Assisted Power Steering  
Fully Independent Hydraulic Outriggers  
5Th Front Outrigger  
Removable Aluminum Outrigger Pads  
Tail swing only 12-Ft  
Remote Outrigger Controls

### Boom Dolly Provision

Boom Float Kit-Dolly Prep  
Emergency Air Shut-Off

### Lower Cab Features

One Man Aluminum Cab  
With Air Conditioning  
Mounted On Vibration Absorbing Pads  
Optimum Visibility With Safety Glass  
Acoustical Foam Padding Inside Cab  
Insulation Against Sound And Weather  
Hot Air Defroster  
Six Way Adjustable Mechanical Suspension Seat  
Lockable Door With Roll Down Window

### Uper Cab Features

Hydraulic AC And LP Heat  
360-Degree House Lock Standard  
Circuit Breakers Located In Cab  
Removable Front Window  
Hinged Tinted Glass Skylight  
Sliding Right-Hand Window  
Armrest Mounted Controls For  
Hoists, Swing And Boom Elevation  
Foot Control Pedals For  
Swing Brake, Boom Telescope And Throttle  
Rated Capacity Indicator System With Digital  
Readout Display And Work Area Definition  
Program  
Anti-Two Block System With Audible And Visual  
Warning And Automatic Function Disconnects

### Option

2-Axle Boom Dolly Add: \$42,900

### Counterweight

Standard Upper Counterweight Package  
With Auxiliary Hoist 10,400 Lb

### Hoist

533 Fpm (163 M/Min) Maximum Line Speed  
15,639 Lb Maximum Line Pull  
Electronic Drum Indicators  
Integral Automatic Brakes  
Two Speed Main And Auxiliary Hoists  
Grooved Drum, Tapered Flanges, And Spring Loaded Cable Roller  
Electronic Hoist Rotation Indicator  
3Rd Wrap Indicator  
500' x 5/8 Spin Resistant Cable  
7 Ton Load Ball With Hook  
5-Sheave (60 Ton) Load Block

### Boom

Lifting Capacity 60 Tons  
110' Four Section, Full Power, Mechanically Synchronized Boom  
High Strength, Four Plate Construction  
To Reduce Weight And Increase Strength  
Quick-Reeving Boom Head  
Hoist Cylinder Is Equipped With Integral Hold Valves  
Auxiliary Sheave Boom Head Assembly

### Jib

33'-57' (2Piece) Offsetting Jib

### Hydraulic System

High Capacity Full Flow Oil Filtration System  
117 Gallon Capacity Reservoir  
Three Gear Pumps Driven Off The Transmission

855-399-5991 -- [www.loadkingmfg.com](http://www.loadkingmfg.com)

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.  
Pictures are representative and may not be identical.

• • PRICE: \$799,900  
• •  
• • Ex Works: Kansas City, MO

QUOTE NUMBER: HC6.11-D\_19

EXPIRATION DATE: 6-30-19