



Load King 80-126TC

80Ton Boom

CRANE SPECIFICATIONS

Engine

Detroit Diesel DD13 450HP
6-Cylinder
Intercooled Turbo Charger

Transmission

Eaton 11 Speed
Ultra Shift Transmission

Fuel Tanks

100 Gallon Fuel Tank

Carrier

8X4 Drive
Box Type Chassis Construction
Full Aluminum Decking
Eaton 11 Speed Transmission
Hydraulic Assisted Power Steering
Fully Independent Hydraulic Outriggers
5Th Front Outrigger
Removable Aluminum Outrigger Pads
Tail swing only 13Ft 10In
Remote Outrigger Controls

Boom Dolly Provision

Boom Float Kit-Dolly Prep
Emergency Air Shut-Off

Lower Cab Features

One Man Aluminum Cab
With Air Conditioning
Mounted On Vibration Absorbing Pads
Optimum Visibility With Safety Glass
Acoustical Foam Padding Inside Cab
Insulation Against Sound And Weather
Hot Air Defroster
Six Way Adjustable Mechanical Suspension Seat
Lockable Door With Roll Down Window

Upper Cab Features

Hydraulic AC And LP Heat
360-Degree House Lock Standard
Circuit Breakers Located In Cab
Removable Front Window
Hinged Tinted Glass Skylight
Sliding Right-Hand Window
Armrest Mounted Controls For
Hoists, Swing And Boom Elevation
Foot Control Pedals For
Swing Brake, Boom Telescope And Throttle
Rated Capacity Indicator System With Digital
Readout Display And Work Area Definition Program
Anti-Two Block System With Audible And Visual
Warning And Automatic Function Disconnects

Option

2-Axle Boom Dolly Add: \$42,900

Counterweight

Standard Upper Counterweight
15,000 Lb

Hoist

460Fpm (162.5 M/Min) Maximum Line Speed
18,450 Lb Maximum Line Pull
Electronic Drum Indicators
Integral Automatic Brakes
Two Speed Main And Auxiliary Hoists
Grooved Drum, Tapered Flanges, And Spring Loaded Cable Roller
Electronic Hoist Rotation Indicator
3Rd Wrap Indicator
600' x 5/8 Spin Resistant Cable
12 Ton Load Ball With Hook
5-Sheave (80 Ton) Load Block

Boom

Lifting Capacity 80 Tons
126' Four Section, Full Power, Mechanically Synchronized Boom
High Strength, Four Plate Construction
To Reduce Weight And Increase Strength
Quick-Reeving Boom Head
Hoist Cylinder Is Equipped With Integral Hold Valves
Auxiliary Sheave Boom Head Assembly

Jib

33'-57' (2Piece) Offsetting Jib

Hydraulic System

High Capacity Full Flow Oil Filtration System
202 Gallon Capacity Reservoir
Three Gear Pumps Driven Off The Transmission

855-399-5991 -- www.loadkingmfg.com

DISCLAIMER: Specifications are believed to be correct, but may contain errors and/or omissions.
Pictures are representative and may not be identical.

• • PRICE: \$953,900
• •
• • Ex Works: Kansas City, MO

QUOTE NUMBER: HC7.11-D_19

EXPIRATION DATE: 6-30-19