

light on your work

X-START
4x1000W MH - 9M



TRIME

Lighting Tower Specialist



X-START 4x1000W MH - 9M

Our engineers know that the market needs a lighting tower that is rugged, long lasting and safe. The X-START has been created beginning from these characteristics. It is the best solution to your needs and guarantees 4200 sqm of illuminated area. 10 units can be loaded on a standard truck. To all of this, we added the technology that allows for maximum fuel efficiency and reliability.



8,5 m



795 Kg



340°



4200 sqm



80(l) - 1,85(l/h)

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8,5 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions for easy handling & transportability, up to 10 units per truck
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization

APPLICATIONS



Gas, oil & mining operations



Special events



Rural & hard to reach areas



Emergency response



Construction & work sites



Military applications



Illuminated area
4200 sqm



**Ease of transport
and handling**



**10
Units Per Truck**




**You can place 10 units on a
single vehicle thanks to one
of the compactest footprints
on the market.**

KEY BENEFITS

✓ *Easy to move*

✓ *Robustness*

✓ *Versatile*



technical data

Dimensions & weight

Dimensions min. (mm)	2560x1320x2550
Dimensions max. (mm)	2560x2550x8500
Total weight without fuel	795 Kg

Features

Rotation	340°
Floodlights	4x1000W
Lamps	Metal halide
Options	Homologated road trailer

Alternator

Model	Synchronous
Frequency (Hz)	50
Insulation class	H
Degree of protection	IP23
Single phase voltage	8 kVA - 230V
Auxiliary outlets	3 kVA

Engine

Model	Kubota D1105
Fuel	Diesel
r.p.m	1500
Tank capacity (l)	80
Consumption (l/h)	1,85
Running time (h)	43
Noise level (dBA) at 7m	68

Standard load delivery


10 sets



Units Per Truck

Illuminated area (5 lux min.)

4200 sqm



Lighting Tower **Specialist**

TRIME s.p.a.

Strada per Robecco, snc
 20081 Cassinetta di Lugagnano (MI)
 Tel. +39 02 942 1724
 www.trime.it - info@trime.it