



VELCRO® Brand

# ALFA-LOK™ Fasteners with SilverTape GP11W Adhesive




## Features

- Free positionable, re-closable fastening system
- High Performance double sided acrylic foam tape
- Suitable for high and medium surface energy material such as glass, metals and several plastics

## Compatibility Surfaces

SUBSTRATES	VELCRO® Brand ALFA-LOK™ Fastener
GLASS	+
ALUMINUM (ANODIZED, RAW)	+
STEEL (STAINLESS, GALVANIZED)	+
PLYWOOD / MDF	+
FORMICA (POLISHED SIDE)	+
CARDBOARD	+
PAINTED WALLBOARD	+
CONCRETE	+
STONE	+
ABS	+
POLYESTER	+
VINYL	+
POLYACRYLIC / PMMA	+
POLYCARBONATE	+
POLYETHYLENE	-
POLYPROPYLENE	-
FABRICS	-

## Performance Specifications

Testing	Minimum Value
BASE MATERIAL	Modified Solvent based Acrylic Polymer
ADHESIVE COLOR	White
TEMPERATURE RANGE OF USE 	Long Term: -40 - +194 °F Short Term: 248 °F
PEEL 180° ADHESION (FINAT-FMT 01) (AVERAGE) 	6 PIW * 8 PIW * - (after 24 h)
SOFTENING POINT	194 °F
STATIC SHEAR (ASTM 3654)** 	2 LB at 70 °F 1 LB at 150 & 200 °F 0.5 LB at 250 °F
TACK	Medium/Low
APPLICATION METHOD	Pressure
APPLICATION	High / Med surface energy, general use

\* Average according typical values. The specifications are as a reference and are pending to confirm.

\*\* Weight that ½ square inch will hold 10,000 minutes (7 days).




+ Recommended - Not Recommended





VELCRO® Brand  
**ALFA-LOK™ Fasteners**  
 Closure Characteristics



CHARACTERISTICS	VELCRO® Brand ALFA-LOK™ Fastener
DENSITY	19 heads/in2
CONSTRUCTION	Woven quadrilobal mushroom tape
BASE MATERIAL	<b>Base:</b> Polyester
	<b>Mushrooms:</b> Polypropylene
FASTENER	Self-engaging
CYCLE LIFE	-
PEEL STRENGTH (AVERAGE) 	1 PIW
SHEAR STRENGTH (AVERAGE) 	72 PSI
TENSILE DISENGAGEMENT (AVERAGE) 	58 PSI
STANDARD COLORS	Black
STANDARD WIDTHS	25mm
STANDARD PUT-UPS	25 yard rolls with flanges
	Cut pieces (customized)



**GLOBAL OFFICES**

**Worldwide Headquarters**

VIL Ltd  
 2 Kingdom Street – 6th Floor  
 Paddington  
 London – W2 6JP  
 United Kingdom  
 Tel: (+44) 203 580 4265  
 Velcro.com

**Global Services Office**

Velcro Group Corporation  
 265 Franklin Street – 19th Floor  
 Boston – MA 02110  
 USA  
 Tel: (+1) 617 946 5501  
 Velcro.com

**AMERICAS**

**USA**

Velcro USA Inc.  
 Tel: (+1) 800 225 0180  
 marketing@velcro.com  
 Velcro.com

**Canada**

Velcro Canada Inc.  
 Tel: (+1) 800 683 5276  
 canada@velcro.com  
 Velcro.com

**Mexico**

Velcro de México, S.A. de C.V.  
 Tel: (+52) 55 5005 3300  
 velcrodemexico@velcro.com  
 Velcrodemexico.com

**Brazil**

Velcro Brasil Ltda.  
 São Paulo  
 Tel: (+55) 11 4195 6644  
 contato@velcro.com  
 Velcro.com.br

Sapiranga  
 Tel: (+55) 51 3599 1483  
 contato@velcro.com  
 Velcro.com.br

**Uruguay**

Velcro Industrial  
 del Uruguay S.A.  
 Tel: (+598) 2288 0008  
 infovurg@velcro.com  
 Velcro.com

**EMEA**

**Spain**

Velcro Europe S.A.  
 Tel: (+34) 93 758 32 98  
 infovesa@velcro.com  
 Velcro.es

**Germany**

Velcro GmbH  
 Freiberg am Neckar  
 Tel: (+49) 7141 991 19-0  
 infovgmbh@velcro.com  
 Velcro.de

**Gronau**

Tel: (+49) 2562 96 45-0  
 infovgmbh@velcro.com  
 Velcro.de

**France**

Velcro Industries France S.A.S.  
 Tel: (+33) 1 34 38 78 88  
 infovif@velcro.com  
 Velcro.fr

**Belgium**

Alfatex N.V.  
 Tel: (+32) 9 386 12 18  
 infofe@velcro.com  
 Alfatex.com

**Italy**

Velcro Italia, S.R.L.  
 Tel: (+39) 039 62 70 01  
 infoveit@velcro.com  
 Velcro.it

**UK**

Velcro Ltd.  
 Tel: (+44) 1606 73 88 06  
 infovlt@velcro.com  
 Velcro.co.uk

**Poland**

Alfatex Sp. z o.o.  
 Tel: (+48) 71 798 57 89  
 infovpl@velcro.com  
 Alfatex.pl

**APAC**

**Australia**

Velcro Australia Pty. Ltd.  
 Tel: (+61) 3 9703 2466  
 sales@velcro.com.au  
 Velcro.com.au

**China**

Velcro China Fastening  
 Systems Company Limited  
 Tel: (+86) 21 6045 2090  
 (Shanghai Sales Office)  
 chinamarketing@velcro.com  
 Velcro.com.cn

**Hong Kong**

Velcro Hong Kong Ltd.  
 Tel: (+852) 2570 3698  
 hkenquiry@velcro.com  
 Velcro.com.hk