

# PRO Mini-Domes



## Features That Make a Difference:

- Superior low light performance
- Face detection and blur detection
- 3 and 5 megapixel resolutions
- Quick and easy installation and configuration
- One-touch focus and motorized zoom
- Multiple motorized lens options
- Reduced storage cost with H.264 and integrated region of interest (ROI) bandwidth management analytics
- Up to five individual programmable regions of interest
- True WDR in 3MP Mini-Dome options
- IP66 and IK10 ratings

The Illustra Pro IP Mini-Domes provide crisp and clear high-definition video, at full frame rates. Whether in bright sun, near darkness or blackout conditions, you can clearly see important details, such as license plates, merchandise labels, and faces.

Installation is simple and easy with no additional cost or hardware. The cameras include various integrated mounting options including hard surface and electric box. On indoor cameras, a plenum cap is included as well as mounting clips for recessed flush installation. Configuration is simplified using the most common web browsers to access the browser-based camera interface for feature control including one-touch focus and

motorized zoom. Illustra Connect, a powerful remote management and configuration software tool, makes set up and installation even easier.

Using onboard motion-detection, and advanced, integrated analytics, the Illustra Pro Mini-Domes reduce your ongoing cost of operation by minimizing the cost of storage while ensuring image quality. The IP66 and IK10 rated outdoor Mini-Domes are rugged and durable providing a vandal resistant enclosure, water ingress protection, and dust ingress protection. The Mini-Domes can be powered using PoE or 24Vac. The outdoor Mini-Dome can operate in temperatures as low as -40°C when powered using 24Vac.




# Specifications

| Spec                            | Indoor   |                   |                         |                   | Outdoor  |  |                 |  |
|---------------------------------|--|-------------------|-------------------------|-------------------|--|--|-----------------|--|
| <b>Operational</b>              |  |                   |                         |                   |  |  |                 |  |
| Video Compression               | H.264, MJPEG   |                   |                         |                   | H.264, MJPEG   |  |                 |  |
| Max Frame Rate (primary stream) | <b>3MP</b>   |                   | <b>5MP</b>              |                   | <b>3MP</b>   |  | <b>5MP</b>      |  |
| H.264                           | 2048x1536@30fps  |                   | 2592x1944@15fps         |                   | 2048x1536@30fps  |  | 2592x1944@15fps |  |
| MJPEG                           | 1920x1440@30fps  |                   | 1920x1440@15fps         |                   | 1920x1440@30fps  |  | 1920x1440@15fps |  |
| ONVIF-Compliant                 | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Analogue Video Output           | 1.0 Vp-p, BNC pigtail included   |                   |                         |                   | 1.0 Vp-p, BNC pigtail included   |  |                 |  |
| Resolution                      | <b>3MP and 5MP</b>   |                   |                         |                   |  |  |                 |  |
|                                 | (2048x1536) QXGA 4:3   |                   | (1920x1080) 1080p 16:9  |                   | (768x576) 4:3  |  | (384x288) 4:3   |  |
|                                 | (1920x1440) 4:3  |                   | (1280x720) 720p 16:9    |                   | (640x480) 640 VGA 4:3  |  | (384x216) 16:9  |  |
|                                 | (1600x1200) UXGA 4:3   |                   | (1024x768) 1024 XGA 4:3 |                   | (640x360) nHD 16:9   |  |                 |  |
|                                 | (1280x960) SXGA 4:3  |                   | (1024x576) PAL+ 16:9    |                   | (480x360) 480 4:3  |  |                 |  |
|                                 | <b>5MP (and all resolutions listed above)</b>  |                   |                         |                   |  |  |                 |  |
|                                 | (2592x1944) 4:3  |                   |                         |                   |  |  |                 |  |
| Imager                          | 1/3.2" CMOS progressive scan   |                   |                         |                   | 1/3.2" CMOS progressive scan   |  |                 |  |
| Day/Night                       | Yes  |                   |                         |                   | Yes  |  |                 |  |
| IR Illumination Optional        | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Motion Detection                | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Face Detection                  | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Privacy Zones                   | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Alarms I/O                      | 2/1  |                   |                         |                   | 2/1  |  |                 |  |
| Video Streams                   | 3 streams plus analog out  |                   |                         |                   | 3 streams plus analog out  |  |                 |  |
| Minimum Illumination            | <b>3MP 3-9mm</b>   | <b>3MP 9-22mm</b> | <b>5MP 3-9mm</b>        | <b>5MP 9-22mm</b> | <b>3-9mm</b>   |  |                 |  |
| Color                           | 0.05 lux   | 0.06 lux          | 0.3 lux                 | 0.4 lux           | 0.3 lux  |  |                 |  |
| B/W                             | 0.003 lux  | 0.004 lux         | 0.02 lux                | 0.03 lux          | 0.02 lux   |  |                 |  |
| With IR                         | -  | -                 | -                       | -                 | 0.0 lux  |  |                 |  |
| Dynamic Range                   | 3MP: TWDR 96dB<br>5MP: WDR 90dB  |                   |                         |                   | 3MP: TWDR 96dB<br>5MP: WDR 90dB  |  |                 |  |
| Field of View (H/V)             | <b>3-9mm</b>   |                   | <b>9-22mm</b>           |                   | <b>3-9mm</b>   |  |                 |  |
| Wide Angle                      | 88°/64°  |                   | 28°/21°                 |                   | 88°/64°  |  |                 |  |
| Telephoto                       | 30°/22°  |                   | 12°/9°                  |                   | 30°/23°  |  |                 |  |
| Lens Type                       | Motorized varifocal  |                   |                         |                   | Motorized varifocal  |  |                 |  |
| <b>Network</b>                  |  |                   |                         |                   |  |  |                 |  |
| Interface                       | Ethernet 10/100Base-TX   |                   |                         |                   | Ethernet 10/100Base-TX   |  |                 |  |
| Ethernet Port                   | RJ-45  |                   |                         |                   | RJ-45  |  |                 |  |
| Supported Protocols             | TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, TLS, Unicast, Multicast, NTP, SMTP, WS-Security |                   |                         |                   | TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, TLS, Unicast, Multicast, NTP, SMTP, WS-Security |  |                 |  |
| <b>Configuration Management</b> |  |                   |                         |                   |  |  |                 |  |
| Web Browser                     | IE 10, 11, Firefox, Chrome   |                   |                         |                   | IE 10, 11, Firefox, Chrome   |  |                 |  |
| Security                        | Multi-level, IP address filtering, HTTPS, User access log, IEEE 802.1x   |                   |                         |                   | Multi-level, IP address filtering, HTTPS, User access log, IEEE 802.1x   |  |                 |  |
| <b>Onboard Storage</b>          |  |                   |                         |                   |  |  |                 |  |
| Card Support                    | Standard SD format up to 4GB, SDHC format up to 32GBytes and SDXC up to 128GBytes  |                   |                         |                   | Standard SD format up to 4GB, SDHC format up to 32GBytes and SDXC up to 128GBytes  |  |                 |  |
| Pre-alarm Recording             | Yes  |                   |                         |                   | Yes  |  |                 |  |
| Recording Format                | AVI  |                   |                         |                   | AVI  |  |                 |  |
| Playback                        | Via browser using FTP  |                   |                         |                   | Via browser using FTP  |  |                 |  |
| Recording Trigger               | Dry contact alarms, motion detection, face detection   |                   |                         |                   | Dry contact alarms, motion detection, face detection   |  |                 |  |
| <b>Simultaneous Users</b>       |  |                   |                         |                   |  |  |                 |  |
|                                 | Ten  |                   |                         |                   | Ten  |  |                 |  |
| <b>Electrical</b>               |  |                   |                         |                   |  |  |                 |  |
| Power Input                     | 24VAC, PoE IEEE 802.3af Class 3  |                   |                         |                   | 24VAC, PoE IEEE 802.3af Class 3  |  |                 |  |
| Power Draw                      | 12.95W   |                   |                         |                   | 12.95W   |  |                 |  |
| <b>Physical</b>                 |  |                   |                         |                   |  |  |                 |  |
| Dimensions (WxH)                | 130 x 138 mm (5.12 x 5.43 in)  |                   |                         |                   | 135 x 160 mm (5.31 x 6.30 in)  |  |                 |  |
| Weight                          | 1 kg (2.20 lbs)  |                   |                         |                   | 1.8 kg (3.97 lbs)  |  |                 |  |
| Housing Color                   | White or black   |                   |                         |                   | White or black   |  |                 |  |
| Operating Temperature           | -10° to 40°C (14° to 104°F)  |                   |                         |                   | PoE: -30° to 50°C (-22° to 122°F)<br>24VAC: -40° to 50°C (-40° to 122°F)   |  |                 |  |
| Vandal Resistant                | IK10   |                   |                         |                   | IK10   |  |                 |  |
| Outdoor Rating                  | N/A  |                   |                         |                   | IP66   |  |                 |  |
| Plenum-Rated                    | Yes  |                   |                         |                   | N/A  |  |                 |  |
| <b>Regulatory</b>               |  |                   |                         |                   |  |  |                 |  |
| Emissions                       | EN 55022 Class A; FCC Part 15 Class A;<br>ICES-003/NMB-003 Class A; AS/NZS CISPR 22 Class A                                  |                   |                         |                   | EN 55022 Class A; FCC Part 15 Class A;<br>ICES-003/NMB-003 Class A; AS/NZS CISPR 22 Class A                                  |  |                 |  |
| Immunity                        | EN 50130-4; EN55024  |                   |                         |                   | EN 50130-4; EN55024  |  |                 |  |
| Safety                          | EN 60950-1; UL 60950-1<br>CSA 22.2 No. 60950-1; IEC 60950-1  |                   |                         |                   | EN 60950-1; UL 60950-1<br>CSA 22.2 No. 60950-1; IEC 60950-1  |  |                 |  |

# Mounts and Accessories

## Pendant / Gooseneck Mounts



Integrated recessed mount

### Mounting Options

| Mount       | Image | Model Number                   | Description                                       |
|-------------|-------|--------------------------------|---|
| Flush Mount |       | ADCiM6FLUSHOW<br>ADCiM6FLUSHOB | Flush Mount Kit:<br>Outdoor Dome,<br>White/Black  |
| Pendant Cap |       | ADCi6DPCAPIW<br>ADCi6DPCAPIB   | Pendant Cap:<br>Indoor,<br>White/Black            |
|             |       | ADCi6DPCAPOW<br>ADCi6DPCAPOB   | Pendant Cap:<br>Outdoor,<br>White/Black           |
| Wall Mount  |       | ADCiM6WALLWK<br>ADCiM6WALLBK   | Wall Mount Kit:<br>Indoor/Outdoor,<br>White/Black |

### Accessories

| Adapter                      | Image | Model Number                         | Description  |
|------------------------------|-------|--------------------------------------|--|
| Gooseneck Arm                |       | ADLOMARM - White<br>ADCBMARM - Black | For use with<br>Pendant Cap  |
| Outside Corner Mount Adapter |       | ADCDMCRNRO                           | For use with Pendant<br>Cap and Gooseneck<br>Arm, or directly to the<br>camera back plate.   |
| Electrical Box Adapter       |       | ADCPWMELEC                           | Use with additional<br>mounting options<br>such as the UK<br>single- and double-<br>gang boxes. This<br>provides a threaded<br>connection directly to<br>the rear of the Illustra<br>600/610 back plate<br>and versatile screw<br>options. |
| Pole Mount Adapter           |       | ADCDMPOLE                            | For use with Pendant<br>Cap and Gooseneck<br>Arm, or directly to the<br>camera back plate.   |

### ILLUSTRA CAMERA MODEL KEY

| ILLUSTRA | SERIES         | MODEL        | RESOLUTION | FORM FACTOR       | LENS         | ENVIRONMENT HOUSING   | BUBBLE     | COLOR      | DAY/NIGHT/IR       | WDR                             | OTHER               |
|----------|----------------|--------------|------------|-------------------|--------------|-----------------------|------------|------------|--------------------|---------------------------------|---------------------|
| I        | E = Essentials | L = Lite     | 01 = 1MP   | B = Bullet        | N = None     | N = None              | N = None   | B = Black  | C = Color Only     | N = No                          | A = Hardware Update |
|          | F = Flex       | P = Plus     | 02 = 2MP   | C = Compact Dome  | F = Fixed    | A = Indoor NonVandal  | C = Clear  | G = Gray   | I = TDN w/IR       | T = Multi-Exposure (>60 Frames) |                     |
|          | P = Pro        | S = Standard | 03 = 3MP   | D = Dome          | 0 = 1.8–3mm  | B = Outdoor NonVandal | S = Smoked | S = Silver | S = Soft Day/Night | Y = Yes                         |                     |
|          | Q = Edge       |              | 05 = 5MP   | F = Fisheye       | 1 = 2.8–12mm | I = Indoor Vandal     |            | W = White  | T = TDN            |                                 |                     |
|          |                |              |            | M = Mini-Bullet   | 2 = 3–9mm    | O = Outdoor Vandal    |            |            |                    |                                 |                     |
|          |                |              |            | P = PTZ           | 3 = 9–22mm   |                       |            |            |                    |                                 |                     |
|          |                |              |            | W = Wireless Cube | 4 = 9–40mm   |                       |            |            |                    |                                 |                     |
|          |                |              |            | X = Box           | 5 = 20x      |                       |            |            |                    |                                 |                     |
|          |                |              |            |                   | 6 = 30x      |                       |            |            |                    |                                 |                     |

### 3 MP Mini-Domes

|              |   |
|--------------|---|
| IPS03D2ICWTT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, clear, white, TDN, TWDR        |
| IPS03D2ICWIT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, clear, white, TDN w/IR, TWDR   |
| IPS03D2OCWTT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, clear, white, TDN, TWDR       |
| IPS03D2OCWIT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, clear, white, TDN w/IR, TWDR  |
| IPS03D2ISWTT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, smoked, white, TDN, TWDR       |
| IPS03D2ISWIT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, smoked, white, TDN w/IR, TWDR  |
| IPS03D2OSWTT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, smoked, white, TDN, TWDR      |
| IPS03D2OSWIT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, smoked, white, TDN w/IR, TWDR |
| IPS03D2ICBTT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, clear, black, TDN, TWDR        |
| IPS03D2ICBIT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, clear, black, TDN w/IR, TWDR   |
| IPS03D2OCBTT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, clear, black, TDN, TWDR       |
| IPS03D2OCBIT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, clear, black, TDN w/IR, TWDR  |
| IPS03D2ISBTT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, smoked, black, TDN, TWDR       |
| IPS03D2ISBIT | Illustra Pro 3MP Mini-dome, 3-9mm, indoor, vandal, smoked, black, TDN w/IR, TWDR  |
| IPS03D2OSBTT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, smoked, black, TDN, TWDR      |
| IPS03D2OSBIT | Illustra Pro 3MP Mini-dome, 3-9mm, outdoor, vandal, smoked, black, TDN w/IR, TWDR |
| IPS03D3ICWTT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, clear, white, TDN, TWDR       |
| IPS03D3ICWIT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, clear, white, TDN w/IR, TWDR  |
| IPS03D3ISWTT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, smoked, white, TDN, TWDR      |
| IPS03D3ISWIT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, smoked, white, TDN w/IR, TWDR |
| IPS03D3ICBTT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, clear, black, TDN, TWDR       |
| IPS03D3ICBIT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, clear, black, TDN w/IR, TWDR  |
| IPS03D3ISBTT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, smoked, black, TDN, TWDR      |
| IPS03D3ISBIT | Illustra Pro 3MP Mini-dome, 9-22mm, indoor, vandal, smoked, black, TDN w/IR, TWDR |

### 5 MP Mini-Domes

|              |  |
|--------------|--|
| IPS05D2ICWTY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, clear, white, TDN, WDR        |
| IPS05D2ICWIY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, clear, white, TDN w/IR, WDR   |
| IPS05D2OCWTY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, clear, white, TDN, WDR       |
| IPS05D2OCWIY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, clear, white, TDN w/IR, WDR  |
| IPS05D2ISWTY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, smoked, white, TDN, WDR       |
| IPS05D2ISWIY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, smoked, white, TDN w/IR, WDR  |
| IPS05D2OSWTY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, smoked, white, TDN, WDR      |
| IPS05D2OSWIY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, smoked, white, TDN w/IR, WDR |
| IPS05D2ICBTY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, clear, black, TDN, WDR        |
| IPS05D2ICBIY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, clear, black, TDN w/IR, WDR   |
| IPS05D2OCBTY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, clear, black, TDN, WDR       |
| IPS05D2OCBIY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, clear, black, TDN w/IR, WDR  |
| IPS05D2ISBTY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, smoked, black, TDN, WDR       |
| IPS05D2ISBIY | Illustra Pro 5MP Mini-dome, 3-9mm, indoor, vandal, smoked, black, TDN w/IR, WDR  |
| IPS05D2OSBTY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, smoked, black, TDN, WDR      |
| IPS05D2OSBIY | Illustra Pro 5MP Mini-dome, 3-9mm, outdoor, vandal, smoked, black, TDN w/IR, WDR |
| IPS05D3ICWTY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, clear, white, TDN, WDR       |
| IPS05D3ICWIY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, clear, white, TDN w/IR, WDR  |
| IPS05D3ISWTY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, smoked, white, TDN, WDR      |
| IPS05D3ISWIY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, smoked, white, TDN w/IR, WDR |
| IPS05D3ICBTY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, clear, black, TDN, WDR       |
| IPS05D3ICBIY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, clear, black, TDN w/IR, WDR  |
| IPS05D3ISBTY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, smoked, black, TDN, WDR      |
| IPS05D3ISBIY | Illustra Pro 5MP Mini-dome, 9-22mm, indoor, vandal, smoked, black, TDN w/IR, WDR |

### Related Products



VideoEdge NVR



victor



exacqVision  
VMS

### Approvals



Driving network video through global standardization

[www.illustracameras.com](http://www.illustracameras.com)