

Copper Certification*



Certifier10G™



Certifier40G™

Tier 1 and Tier 2 Fiber Certification*



SmartClass Fiber OLTS-85



SmartClass Fiber MPOLx



Certifier40G



T-BERD/MTS-2000

Essential Fiber Tools

Fiber Inspection



Probe microscope
P5000i

FiberChek™

SmartClass Fiber
HD4iP

VFL



Visual fault locator
FFL-050

LFI



Live fiber Identifier
FI-60

Optical Power Measurement



Power meter
MP-60A

SmartPocket™

PowerChek™

Test Solutions for Structured Cabling

Copper Certification

Feature	Certifier10G	Certifier40G
Up to Category 6A/Class EA channel and link certification	■	■
Up to Category 7A/Class FA channel and link certification		■
Up to Category 8 channel and link certification		■
Patch cord certification	■	■
Coax certification	■	■
Test result management and reporting	■	■

Tier 1 and Tier 2 Fiber Certification

Feature	OLTS-85	MPOLx	Certifier40G	T-BERD/ MTS-2000
Fiber end-face inspection (with P5000i)	■	■	■	■
Dedicated fiber patch cord microscope	■	■		
Tier 1 fiber certification	■	■	■	
Encircled flux compliant	■	■	■	
Copper certification			■	
12 fiber MPO length/loss/polarity (multimode)		■	■	
Tier 2 fiber certification				■
Test result management and reporting	■	■	■	■

Essential Fiber Tools

Fiber Inspection

Feature	P5000i	FiberChek	SmartClass Fiber HD4iP
Dual magnification inspection of fiber end faces	■	■	■
Pass/fail analysis to industry standards or custom requirements	■	■	■
Compatible with mobile devices	■	■	■
On-board storage		■	■
Integrated display		■	■
Dedicated fiber patch cord microscope			■
Test result reporting	■	■	■
Wireless operation		■	

Optical Power Meters (OPM)

Feature	MP-60A	SmartPocket	PowerChek
Broadband optical power measurement	■	■	■
Absolute and reference-level measurement	■	■	■
On-board results storage		■	■
Optical source		■	
Integrated display		■	■
In-bulkhead, non-contact test			■
Test result reporting	■	■	■

Visual Fault Locator

Feature	FFL-050
Locate sharp bends, breaks, and damages in fiber	■
Conduct end-to-end continuity tests	■
1 mW laser for single-mode and multimode applications	■

Live Fiber Identifier

Feature	FI-60A
Detect optical signals without having to disconnect the fiber	■
Ensure safe engagement with locking	■
Accepts multiple cable diameters (250 um to 3 mm jacketed fiber) without changing dies or inserts	■
Also functions as an optical power meter	■



Contact Us **+1 844 GO VIAVI**
(+1 844 468 4284)

To reach the Viavi office nearest you,
visit viavisolutions.com/contacts.

© 2017 Viavi Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
enterprise-lc-net-tm-ae
30168203 908 0517

viavisolutions.com