

A WORLD LEADER IN CATALYST SUPPORT MEDIA AND TOWER PACKING

## T-86 PROX-SVERS<sup>®</sup>

- Ceramic inert support balls used for moderate temperature applications (up to 1800°F/ 982°C) such as dehydration or desulfurization as well as strongly acidic applications. T-86 is available in sizes 1/8" - 2" (3mm - 50mm).



## T-38 PROX-SVERS<sup>®</sup>

- Premium grade ceramic inert support suitable for use at service temperatures up to 2500°F/ 1370°C with enhanced impact and pressure shock resistance. T-38 is available in sizes 1/8" - 2" (3mm - 50mm).

## T-46 PROX-SVERS<sup>®</sup>

- ~95% alumina, low silica chemically bonded inert support. T-46 is the most thermal and pressure shock resistant alumina ball on the market and is ideal for high temperature applications (up to 3200°F/ 1760°C) with steam such as Secondary Reformers/ATRs. T-46 is available in sizes 1/8" - 3" (3mm - 76mm).



## T-99 PROX-SVERS<sup>®</sup>

- 99.0% and 99.5% alumina, low silica inert support. T-99 is a high density media with very low porosity, high strength and low dust. Suitable for severe, high temperature applications up to 3272 °F/ 1800°C. T-99 is available in sizes 1/16" - 4" (1mm - 100mm).

## CATA-COGS<sup>™</sup>

- Low porosity, high strength, 99% alumina fluted rings with high void fraction to reduce pressure drop. Suitable for high temperature applications up to 3272 °F/ 1800°C. Available in sizes 16mm, 38mm, 76 mm and 85mm.

