## a - DOVER COMPANY

## **OX BUMPER WINCH KIT**

Designed For Skid Steers

Skid steer operators often need retrieval capability or the ability for self-recovery to make their jobs easier. These abilities, along with added protection for the engine compartment, are available with the new OX bumper winch kit. The OX bumper winch has a large 20,000 lbs. capacity for effective self-recovery and object retrieval, a modular and open design that allows full access to the engine without compromising protection and can be easily installed on a variety of skid steer brands and models. And because they are made by dp Winch, a market leader for nearly 50 years, you can rest assured that these winches are rugged and dependable.

## **FEATURES**

- 20,000 lbs (88.9 kN) hydraulically driven planetary winch includes:
  - 74 feet (22.6 m) of 9/16 in (14 mm) wire rope
  - Spring applied cable packer
  - Manual drum kickout for easy free spooling
  - Hawse fairlead plate to reduce rope damage
  - Hoses and hardware for plug-n-play installation
  - Complete assembly under 600 lbs

- Robust frame protects the engine compartment while still permitting easy access
- Open frame design is easy to clean and remove debris with heavy duty hinge
- Industrial grade paint standard
- Custom branding available
- Simple slide latch with pull off anchor pin provides easy swing away feature

salesinfo@dovertwg.com







| LAYER | DRUM CAPACITY<br>(ft) 9/16″ Dia Rope | LINE PULL<br>(k lbs) | LINE SPEED<br>(fpm) | DRUM CAPACITY<br>(m) 14mm Dia Rope | LINE PULL<br>(kN) | LINE SPEED<br>(mpm) |
|-------|--------------------------------------|----------------------|---------------------|------------------------------------|-------------------|---------------------|
| 1     | 20                                   | 20                   | 23                  | 6                                  | 88.9              | 7                   |
| 2     | 45                                   | 16.6                 | 28                  | 13.7                               | 73.8              | 8.5                 |
| 3*    | 74                                   | 14.2                 | 32                  | 22.6                               | 63.2              | 9.8                 |

Ratings are based on 15 gpm and 2750 PSI (57 lpm 190 bar) | Drum capacities are in accordance with SAE J706. \*Layer does not meet SAE J706.



TWG Canada, 19350 22nd Ave Surrey, BC V3Z 3S6 CANADA (604) 547-2100 I salesinfo@dovertwg.com

TWG Headquarters, 11135 S James Ave Jenks, OK 74037 USA (918) 298-8300 I salesinfo@dovertwg.com