



Shingle Plus Features

- Lifetime Limited Warranty
(including 120 mph winds and hail penetration)
- Class 4 Impact Resistance to UL 2218
by Underwriters Laboratories (Highest Rating)
- Lightweight: Only 150 lbs. per 100 sq. ft.
- Non-Combustible Class A Rated Material
- Won't Crack, Break, Burn, Curl, Split or Rot
- Walkable | Low Maintenance | Long Life
- Non-Porous | Freeze/Thaw Resistant
- Overlapping Panels Provide Weather Protection
- Tear-Off May Not Be Required (see local code)
- Direct to Deck Application or on Batten Strips
- Up To 30% Recycled Steel Content

SPECIFICATIONS

Minimum Roof Pitch ➤	3:12
Panel Dimension ➤	16-1/2" x 52"
Installed Exposure ➤	14-1/2" x 50"
Panels per Square ➤	20
Installed Weight ➤	150 lbs. / sq.



WARRANTY, COMPOSITION, EVALUATIONS, TESTING & APPROVALS

Warranties:

- Lifetime Limited Warranty*
- 120 mph Wind Speed Warranty
- Hail Stone Penetration Warranty

**Offered on single family residences in U.S. and Canada;
50 Year Warranty on commercial buildings*

Composition:

- Steel – Aluminum-Zinc Alloy Coating
- Acrylic Primer Coat
- Acrylic Basecoat
- Ceramic Coated Stone Granules
- Clear Acrylic Overglaze

Evaluations, Testing and Approvals:

- See latest list and report links for ICC-ES, Florida Building Code, LA City, Miami-Dade County NOAs at www.decra.com
- Texas Department of Insurance Report RC-281
- Fire: UL 790 (ASTM E108 A,B&C) – Class A Pass
- Hail: UL 2218 Class 4
- Wind Uplift: UL 1897
- Plant: ISO 9001:2008; OHSAS 18001; ISO 14001:2004



AVAILABLE COLORS



Due to lighting and the printing process, roof colors and color swatches may vary from the actual product.

AVAILABLE ACCESSORIES

- Hip & Ridge
- Side Flashing
- Valley & Cap
- Underpan; Flat Sheet
- 3.5" & 5" Fascia Metal Flashing
- Panel Vent; Ridge Vent System
- Color Coordinated Hex Head Screws
- Touch-up Kit