### S&G<sup>®</sup> D-Drive<sup>™</sup> Z<sup>02</sup> Electronic Safe Lock

## Innovative Direct Drive Electronic Safe Lock

#### Why S&G<sup>®</sup> D-Drive™?

- Lock bolt retraction and extension is controlled directly by turning the keypad ring.
- Attach boltwork or a blocking bar directly to the lock bolt or to optional locking bars without fear of overwhelming the lock's drive mechanism or accelerating wear.

#### The Z<sup>02</sup> Direct Drive Advantage:

- An exclusive, no-twist cable design that virtually eliminates the risk of cable damage due to keypad rotation.
- Sure-grip, low profile keypad gives a good, solid feel for the action of the lock.
- Low profile keypad incorporates an open/close indicator to let you know at a glance if the safe is locked or unlocked.
  - UL<sup>®</sup> Type 1 Listed





- Choice of internal or external battery placement. The standard external option puts the battery inside the keypad, where it can be easily changed. Optional internal battery placement puts the battery inside the safe.
- Field installable bolt position indicator (BPI) module is available to let you tie lock action to alarms, video surveillance recorders, etc. The module can be added to a lock at any time, with minimal labor.
- Program the lock from the keypad at any time. No optional, pricey programmer box required.
- The S&G<sup>®</sup> D-Drive<sup>™</sup> lock body is the same size and mounting footprint as other standard S&G locks, allowing for easy retrofit without the need for boltwork or mounting screw location changes.



### Z<sup>02</sup> D-Drive<sup>™</sup> by Sargent and Greenleaf

# Security features plus positive bolt control

#### Choose Your Optimum Mode through the Keypad

#### The **Z<sup>02</sup> D-Drive™ lock** is UL Type 1 Listed. It features: *Three Keypad Selectable Modes of Operation*—

- Multi-User—The Master Code, Supervisor Code, and any User Code can open the lock with a single code.
- Manager/Employee—User Code holders can access the safe only when it's been enabled by a Master Code or Supervisor Code holder.
- Dual Control—Two different lock codes must be entered within one minute of each other to open the safe.

#### Multiple Codes—

• One Master Code, one Supervisor Code, five User Codes, one Time Delay Override Code, and a Management Reset Code.

#### Holdup Protection—

• Time delay is a proven holdup deterrent. The S&G<sup>®</sup> Z<sup>02</sup> D-Drive<sup>™</sup> lock gives you a time delay up to 99 minutes, and a time delay override code for instant cash carrier access.



Optional Bolt Position Indicator (BPI) module can trigger alarms, CCTV recorders, or virtually any relay activated security device.



The lock cable is completely protected in a specially designed channel in the spindle. It can't get caught, pinched, or crimped as the lock is operated day after day.



The lock battery is housed in a special compartment inside the keypad, where it can be easily accessed for changing.



LOCKED (SECURE) INDICATOR

#### OPEN INDICATOR

Sure-grip, low profile keypad incorporates OPEN and CLOSE indicators. You can tell at a glance whether your lock is open or secure.



Protect your assets with the Z<sup>02</sup> D-Drive<sup>™</sup> electronic safe lock.

WWW.Sargentandgreenleaf.com Corporate Headquarters: One Security Drive • Nicholasville, Kentucky 40356 • USA • Tel. 859-885-9411, Fax 859-887-2057 European Headquarters: 9, chemin du Croset • 1024 Ecublens • Switzerland • Tel. 41 21 694 34 00, Fax 41 21 694 34 09

