



Digital Time Lock™ Model 3006/3007/3028/3029

**ADVANCED FLEXIBILITY.
UNCOMPROMISED SECURITY.**

Sargent and Greenleaf's Digital Time Lock gives small businesses and retail outlets all the benefits of a high security, digital solution while expanding flexibility with advanced features. Easily program access schedules, download audit events, and review data in a secure, user-friendly online interface. Digital Time Lock makes securing your assets—and your peace of mind—simple.

FEATURES

- **PINPOINTED ACCESS.** Four opening schedules allow more shift coverage and access control without overriding security.
- **ENHANCED AUDIT DATA.** Digital Time Lock records up to 1000 time- and date-stamped audit events with a quick USB download feature.
- **USER-FRIENDLY INTERFACE.** Digital Time Lock requires no additional software to program. A simple website interface and intuitive process make programming quick and easily transferrable.

Learn more at www.sargentandgreenleaf.com.

Protecting assets from high-security government sites to banks to businesses for more than 150 years, Sargent & Greenleaf continues to set the standard for innovation, security, quality, and trust.

Model 3006/3007/3028/3029

MODEL 3006-302 PIVOTBOLT™

- Automatically re-locks to secure the safe whenever the container's boltwork moves to the fully closed position
- Lock bolt retraction and extension controlled by the movement of the safe's boltwork
- Withstands 225 lbs. of bolt end pressure for a high level of security
- Stainless steel lock bolt



MODEL 3007-302 DIRECT DRIVE™

- Lock bolt retraction and extension controlled by turning of the keypad, offering dependable manual control of the locking bolt
- Exclusive no-twist cable design prevents cable damage during opening
- Withstands 225 lbs. of bolt end pressure for a high level of security



MODEL 3028-302 DEAD LATCHING

- Motor-driven
- Withstands 225 lbs. of bolt-end pressure for a high level of security and durability in boltwork blocking applications
- Does not require direct attachment of the lock bolt to the safe's boltwork



MODEL 3029-302 PUSH/PULL

- Motor-driven
- Designed for direct boltwork attachment
- Push/pull strength of 2.4 lbs. with maximum load of 5.6 lbs.
- Bolt has drilled and tapped holes



SPECIFICATIONS

CERTIFICATIONS

- UL Type 1
 - EN 1300*
 - Vds Class 2*
 - A2P B/E*
 - ECB-S*
 - CNPP*
- *Pending*

CODE MANAGEMENT

- Single Control, Dual Control, and Manager/Employee modes
- Easily assign four independent schedules for up to 100 users
- Four opening windows per day for each schedule
- Program up to 30 holidays
- Management Reset Code
- One hundred million codes available
- User-friendly programming via website interface
- Programmer Code access allows easy review of current settings via large digital display

INSTALLATION

- Standard S & G Magic Module footprint
- Universally handed: left hand, right hand, up, or down mounting

OPERATION

- Motor-blocking bolt operation
- Penalty lockout feature deters random code entry attempts
- Time delay up to 99 minutes
- Powered by two 9V batteries
- Low battery signal
- Integrated user interface uses the display screen and three keypad LEDs, as well as audio signals, to indicate lock status

ADDITIONAL FEATURES

- Non-solenoid construction prevents vibration and bouncing attacks
- Fast USB audit download allows user to view, print, or email audit events
- Bright chrome ring
- Increased clock accuracy

WARRANTY

- Two-year limited warranty

For more information, to find part numbers, or to place an order, visit us online or contact your Sargent and Greenleaf sales representative.

www.sargentandgreenleaf.com

