



NECAL Corporation

Stick with Us

Technical Data Sheet

NECAL 8192 PRESSURE SENSITIVE ADHESIVE

DESCRIPTION

NECAL 8192 is a white or black polyethylene foam supported adhesive with superior tack.

FEATURES

NECAL 8192 is primarily intended for applications with extremely rough substrates such as cast iron, cement, etc. NECAL 8192 has excellent impact and vibration resistance. NECAL 8192 has excellent adhesion to polyethylene and polypropylene as well as other substrates.

PHYSICAL PROPERTIES

Thickness (without liner):	35 mils (total)
Construction:	Rubber based adhesive on both sides of a black or white polyethylene closed-cell foam
Release Liner:	Available with P, W, H, HD, J, VF, P1, H2 or W1 liners
180° Peel from Stainless Steel (both passes):	>5 lbs. after 16 hour dwell (PSTC-101)
Shear Adhesion:	>7 days (1 inch x 1 inch x 1000 g @ 72°F)
Temperature Range:	Application: 50°F. Minimum Service -40°F. to 170°F.

All tests conducted with a 2 mil PET backing

BONDING INSTRUCTIONS

Remove the release liner and apply to a clean, dry substrate. Use firm pressure to obtain maximum contact. Increasing application force will optimize bond strength to surface. The adhesive will reach maximum bond after 72 hours.

STORAGE DATA

The shelf life of this material is at least two years when stored at 72°F and 50% relative humidity. Increased temperatures and/or humidity will affect performance characteristics.

NOTICE

The information shown here represents typical values, which may vary with each application. The values are not intended to be a performance guarantee and are not intended to be utilized for setting specifications. Users should determine, prior to use, the suitability of this material for their application.

March-2018