



Product Service

EU-Type Examination Certificate

No. P5A 089530 0006 Rev. 00

Holder of Certificate: TrueBlue LLC
dba Head Rush Technologies
1835 38th Street
Boulder 80301
USA

Product: PPE against fall from a height
Auto Belay Device

Model(s):
-TruBlue, TB150-12C (7.5m)
-TruBlue, TB150-12C (12.5m)
-TruBlue XL, TBXL150-20A
-TruBlue Speed, TBSD150-20 (12.5m)
-TruBlue Speed, TBSD150-20 (16m)

Tested according to: DIN EN 341:2011
DIN EN 360:2002

The Certification Body of TÜV SÜD Product Service GmbH confirms that the listed product fulfils the basic requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category III). This certificate refers only to the submitted sample for testing and certification and on its technical documentation. See also notes overleaf. The validity of this certificate based on an ongoing surveillance in accordance with Module C2 or D of Regulation (EU) 2016/425 by a Notified Body.

Test report no.: 713149138

Valid until: 2024-03-28

Date, 2019-04-01


(Matthias Völz)

Page 1 of 3

TÜV SÜD Product Service GmbH is Notified Body according to Regulation (EU) 2016/425 on personal protective equipment with the identification number 0123.

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®



Product Service

EU-Type Examination Certificate

No. P5A 089530 0006 Rev. 00

Parameters:

| | |
|-----------------------|---|
| Function principle: | -when climbing tension in the auto belay device descent webbing line is given by the rewind system via rewind spring; -when descending (or falling while climbing) auto belay device controls descent speed of a person by dissipating the potential energy in the eddy current brake; descending speed is not constant, at start the speed is higher than at landing; brake strength of eddy current brake is controlled by reaction springs of rotor blades, which are specific for each version. TruBlue Speed has a redundant free-wheel and less heavy rotor components for better retraction performance (a.e. required for speed climbing competitions); |
| Construction: | self-retracting automatic descender device with central axis, self-retractable descent webbing line, activated by retraction spring, gear transmission to eddy current brake with 3 rotor arms and permanent magnets; central plate (aluminium) with primary and secondary mount and handle; 2 body casings (aluminium), screwed on central plate, with plastic covers; webbing line drum and retraction spring drum; lower webbing line with shackle (28,6mm x 19mm) replaceable by opening nozzle; |
| Descent webbing line: | -TruBlue,: PA-webbing; 20,8 mm wide, 2,31 mm thick; guaranteed break strength: 17,7kN; -TruBlue XL; TruBlue Speed: UHMWPE-webbing; 20,8 mm wide, 1,52 mm thick; guaranteed break strength: 15,5 kN; Upper webbing line in device connected to drum and shackle; lower webbing line (replaceable by client) from shackle to webbing line connector; webbing line end outside device doubled and stitched, with end termination loop with 6 stitching bars; webbing line end length (without connector) and color: -TruBlue, TB150-12C (7.5m): 40 cm, red; -TruBlue, TB150-12C (12.5m): 40 cm, blue; -TruBlue XL, TBXL150-20A: 40 cm, purple; -TruBlue Speed, TBSD150-20 (12.5m): 70 cm, black; -TruBlue Speed, TBSD150-20 (16m): 70 cm, blue; |
| Webbing connector: | directional EN 362-A/T connector with automatic gate locking device (triple-lock) and swivel; stitched into end loop of webbing line; |
| Device measures: | 380 mm x 320 mm x 216 mm; |
| Working load: | -TruBlue, TB150-12C (7.5m): min: 10 kg; max: 150 kg; -TruBlue, TB150-12C (12.5m): min: 10 kg; max: 150 kg; -TruBlue XL, TBXL150-20A: min: 10 kg; max: 136 kg; -TruBlue Speed, TBSD150-20 (12.5m): min: 10 kg; max: 136 kg; -TruBlue Speed, TBSD150-20 (16m): min: 10 kg; max: 136 kg; |

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17

EU-Type Examination Certificate

No. P5A 089530 0006 Rev. 00

| | |
|--------------------------------------|--|
| Min/max. permitted descending speed: | 0.5-2 m/s; |
| Max. tested descent height: | measured from nozzle to ground: -TruBlue, TB150-12C (7.5m): 7.5 m; -TruBlue, TB150-12C (12.5m): 12.5 m; -TruBlue XL, TBXL150-20A: 20.0 m; -TruBlue Speed, TBSD150-20 (12.5m): 12.5 m; -TruBlue Speed, TBSD150-20 (16m): 16.0 m; |
| Min. tested descent height: | measured from nozzle to ground: -TruBlue, TB150-12C (7.5m): 3.5 m; -TruBlue, TB150-12C (12.5m): 7.5 m; -TruBlue XL, TBXL150-20A: 12.0 m; -TruBlue Speed, TBSD150-20 (12.5m): 7.5 m; -TruBlue Speed, TBSD150-20 (16m): min: 12.0 m; |
| Min. temperature: | -4°C; if kept dry: -10°C |
| Weight: | -TruBlue, TB150-12C (7.5m): 20.057 kg (steel-connector); -TruBlue, TB150-12C (12.5m): not measured; -TruBlue XL, TBXL150-20A: 21.244 kg (Alu-connector); -TruBlue Speed, TBSD150-20 (12.5m): not measured; -TruBlue Speed, TBSD150-20 (16m): 19.592 kg (Alu-connector); |
| Marking: | manufacturer address, model, CE-marking, "read instructions"-pictogram; serial no.; manufacturing date; in accordance with EN 341:2011-1A and EN 360: 2002; temperature range; min/ max mounting height; min/ max user weight; max descent rate: 2.0 m/s; on rope EN 341: manufacturing date; manufacturer; |



TruBlue



TruBlue XL



TruBlue Speed

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT