

03A Hydraulic Power Packs

Hydraulic Power Pack Diesel driven LPP 7 HA/B8/w - 226150

The Lamor Power Pack LPP 7 is used as a power source for the range of Lamor skimmers and smaller hydraulically operated equipment. The power pack represents a light-weight, easily portable power solution for hydraulic equipment that can be operated in remote locations.

The LPP 7 is equipped with a max 7.3 kW (9.8 hp) air-cooled single cylinder diesel engine mounted in a mobile frame manufactured in tough tubular steel. An electric start is standard with a manual start as back up.

The LPP 7 comprises 2 hydraulic circuits supplied by an 8 cm³ hydraulic pump and is capable of producing a working pressure of 170 bar with a maximum hydraulic oil flow rate of 28 l/min (7 gpm).

Also the LPP 7 HA can be equipped with optional spark arrestor and/or Chalwyn safety shut down valve.

Standard connectors:

Standard connectors:

Valve 1: 1/4" TEMA 2521/2511, 5 l/min

Valve 2: 1/2" TEMA 5021/5011, 25 l/min

Drain: 3/8" Aeroquip Female ISO C23071-06



TECHNICAL SPECIFICATIONS

Length	945 mm	37 in
Width	850 mm	33 in
Height	785 mm	31 in
Weight	140 kg	309 lbs
Hydraulic flow	28 l/min	7 gpm
Hydraulic pressure	170 bar	2465 psi
Fuel tank volume	5 l	1.3 gal
Wheels	Yes	
Power max	7.3 kW	9.8 hp

BENEFITS

- Light weight and portable
- Multipurpose power source
- Electric start as standard
- Manual back-up start
- Air cooled single cylinder engine
- Robust steel frame
- Four point lifting rings as standard