
Product Category
SKIMMER
VESSEL MOUNTED

Product No 397440 & 397441



## Sweep Skimmer

MOS 25 & 50



## BENEFITS

- Single vessel advancing system
- Operational speed of 4.5 knots
- · Large sweeping width
- Rapid deployment
- Recovers all types of oil
- Modular system
- · Nearshore & offshore
- Wave conforming properties

www.lamor.com

The Lamor and Egersund Group Marine Offshore Sweeper system, MOS, is an innovative, vessel mounted oil spill recovery system that processes whole oil slicks at a time with a 25 or 50 m sweeping width. The unique design allows operation in waves up to 3 m and at towing speeds up to 4.5 knots.

A multi-barrier system, the MOS consists of numerous deflectors organized in a herringbone pattern. This creates hydrodynamic currents that concentrate oil into the recovery channel and guide the contained oil to a skimmer and pump in the apex of the sweeper. Water flow is reduced by a bottom net, increasing the concentration of recovered oil before reaching the skimmer inlet.

The MOS can be operated from supply/offshore supply vessels, fishing vessels, coast guard vessels and stand-by vessels. It is rapidly deployed and ready to use in less than 30 minutes ensuring a fast response to emergency incidents. Containerized systems are available for easy transportation and protected storage. The system has enhanced maneuverability and wave conforming characteristics compared to other conventional booms, and is very cost effective in contrast to systems that need two boats to function.

The MOS Sweeper, when combined with an additional skimmer, pump and ParaVane, is a complete single vessel oil containment and recovery system that can chase, collect, skim and pump oil. There are several systems options, including a brush skimmer addition and a variety of pumps to select from that can be equipped to the Sweeper system.

## Product Category SKIMMER VESSEL MOUNTED

Product No 397440 & 397441





## **TECHNICAL SPECIFICATIONS**

	MOS 25	MOS 50
Sweeping Wldth	25 m (82 ft)	50 m (165 ft)
Length	50 m (164 ft)	100 m (330 ft)
Weight	1400 kg (3090 lbs)	3500 kg (7700 lbs)
Skimming Speed	2,3 m/s (4,5 knots)	2,3 m/s (4,5 knots)
Oil Encounter Rate (in 1 mm oil layer)	208 m³/h (916 gpm)	416 m³/h (1832 gpm)
Wave Heights	0-3 m (0-10 ft)	0-3 m (0-10 ft)
Optional Skimmer*	Various options	Various options
Optional Pump*	115-280 m³/h	140-2x250 m³/h
	(506-1,233 gpm)	(616-2x1,100 gpm)
Optional Paravane*	25/50	50
Optional Reel*	H 2240 or U 2340	U 2358
Optional Collector Pool*	MOS 25	MOS 50
		+0.11% 1.6%





