

Oil Storage Barge LSB 25 S

226454

The LSB 25 floating tank is an inflatable barge for temporary oil storage during oil spill recovery operations. Its storage capacity is 25 m³ (883 ft³). The LSB 25 is a durable long lasting barge manufactured from hypalon neoprene fabric that can be used in extreme climatic conditions and temperatures and moreover, it has exceptional resistance to hydrocarbons.

The design of the barge does not have transoms or rigid stiffeners resulting in excellent flexibility. This design minimizes the possibility of damage to other vessels engaged in pollution control, and also permits minimal volume packaging, while the shape of the lower containment bag ensures easy maneuvering and good handling characteristics.

Inflation and deployment of the barge can be conducted in less than an hour by two persons utilizing e.g. a Lamor air blower. Its bow section with cut-off corners is raised facilitating towing whether the inflatable is empty or fully loaded. Its towing speed is 10 knots when empty and 4.5 knots when loaded. As the barge is filled with recovered oil, the bottom expands forming a pocket. Directional stability during towing operations is provided by the addition of longitudinal keels.



Technical Specifications:

| | | |
|-----------|-------------------|---------------------|
| Length | 9000 mm | 29.5 ft |
| Width | 3960 mm | 13 ft |
| Freeboard | 1150 mm | 3.8 ft |
| Draft | 1700 mm | 5.6 ft |
| Weight | 292 kg | 644 lbs |
| Capacity | 25 m ³ | 883 ft ³ |
| | | |
| | | |
| | | |

Benefits:

- Small footprint while stored
- Easy and fast to deploy
- Easy to tow with good stability
- Strong material withstanding long exposure to hydrocarbons
- Design without transoms and rigid stiffeners minimizing risk of damaging other equipment used in operations