

## Advanced Process Control Instruments Family

### FEATURES

- Three enclosure types: panel mount, desktop, harsh environment
- Modular system with flexible configuration
- Up to 8 weighing/force measurement channels per unit
- Synchronized sampling
- Fast update rate – up to 800 updates per second
- Graphical User Interface – color LCD display with backlight
- Data entry through touch screen and/or functional Keypad
- Integrated flexible digital I/O
- Communication: Ethernet, Profibus, DeviceNet, Modbus, USB, RS485, RS232, Modbus/TCP, EtherNet/IP
- Easy parameter backup and restoration via USB port or internal memory



Panel Mount (PM)

Harsh Environment Enclosure (HE)



### APPLICATIONS

- Process weighing and control
- Force measurement
- Web tension measurement and control
- Automation
- Force vector calculations
- High dynamic force measurement
- High speed batching/blending systems

### DESCRIPTION

The BLH Nobel G4 family of process control instruments offers high speed, high performance control for industrial weighing/force measurement applications plant wide. G4 units set new standards geared for today's application demands and tomorrow's expanding requirements.

A large (5.7 in) color touch screen facilitates quick, easy operation and simplifies parameter changes. The screen displays up to 4 weighing/force channels simultaneously, allowing the user full control of multiple process vessels. The large touch screen provides good visibility of the process and easy navigation through parameter menus and settings.

G4 instruments accommodate up to seven different, easily installed, modules for advanced performance, more functional channels, custom applications, or repair. This provides customers with a highly flexible, upgradeable, single instrument system capable of weighing up to eight independent vessels or scales. Inputs and outputs can be configured according to customer requirements.


A wide variety of industrial communication interfaces (Ethernet, RS232, RS485), Protocols (Modbus RTU, Modbus TCP, EtherNet/IP) and Fieldbuses (Profibus or DeviceNet) are available.

Software upgrades can be downloaded to the instrument from our website, or be transferred to the G4 unit via a standard USB port connection.

Custom software designed to customer requirements for special applications is available upon request.

G4 instruments have four base mounting options: DIN Rail, Panel, Desktop, and Harsh Environment. The last three are IP65 rated, while the DIN rail-mount is IP20 rated. Units can be configured for either 24 VDC or 115/230 VAC operation.

### CONFIGURATION



Document No. : 12207 Revision: 11-Apr-2018

## Advanced Process Control Instruments Family

SPECIFICATIONS		
PARAMETER	VALUE	
Enclosure types	<b>PM</b> Panel mount	<b>HE Harsh</b> Environment
Dimensions W x H x D	294 x 227 x 152 mm	343 x 274 x 235 mm
Enclosure design	Aluminum housing, plastic panel	Stainless steel housing, plastic panel
<b>ENVIRONMENTAL</b>		
Temperature range – Rated performance	–10 to +50°C	
Temperature range – Storage	–25 to +85°C	
Protection	IP65 (panel)	IP65
EMC, Safety	CE (Industrial), UL, cUL, FM, cFM	CE (Industrial), UL, cUL
Display	Color TFT LCD screen with back- lighting, 5.7 in 320 x 240 pixels	
Keyboard	Touch screen and 34 membrane keys	
<b>POWER</b>		
DC SUPPLY module	19–29 VDC, 40 W	
AC SUPPLY module	115/230 VAC 50/60 Hz, 40 W	
<b>CPU MODULE</b>		
Interfaces	Isolated	
RS232 and RS485, ports	For process data and control	
Protocol	Modbus RTU	
Baud rate	Up to 115 kbaud	
USB, supported units	Version 1	
Keyboard	USB keyboard for PC	
Memory stick	USB type for PC For backup and restore of set-up parameters. For change to a new program version	
Ethernet	For process data and control	
Protocol	Modbus TCP and EtherNet/IP	
Field bus options	For process data and control	
Available field busses	Profibus or DeviceNet. Other on demand (contact factory)	
PARAMETER	VALUE	
<b>WF IN1 (1 INPUT) AND WF IN2 (2 INPUTS) WEIGHT/FORCE INPUT MODULES</b>		
Max. no. of load cells	8 per channel	
Excitation voltage	5 VDC	
A/D conversion	3.9 kHz, 16,000,000 units (24 bits)	
Input range	±7 mV/V	
Update rate	1 up to 300 readings per second	
No. of weight channels	1 (WF IN1) up to 8 (4 WF IN2) channels	
Sensitivity	0.1 µV	
Zero drift	<10 nV/V/K	
Span drift	<2 ppm/K	
Digital I/O	4 inputs, 24 V, isolated with common return 2 outputs, 24 V, max. 100 mA, isolated with common return	
<b>HS WF2 HIGH SPEED WEIGHT/FORCE INPUT MODULE</b>		
Max. no. of load cells	4 per channel	
Excitation voltage	10 VDC	
A/D conversion	20 kHz, 16,000,000 units (24 bits)	
Input range	±4.5 mV/V	
Update rate	6 up to 800 readings per second	
No. of weight channels	2 or 4 channels	
Sensitivity	0.1 µV	
Zero drift	<10 nV/V/K	
Span drift	<2 ppm/K	
Type	4 inputs, 24 V, isolated with common return 2 outputs, 24 V, max. 100 mA, isolated with common return	
<b>DIO8 MODULE, DIGITAL INPUT AND OUTPUT MODULE</b>		
Separate I/O module	2 units can be used	
Digital I/O	8 inputs, 24 V, isolated with common return 8 outputs, 24 V, max. 100 mA, isolated with common return	
<b>AOUT1/AOUT4 ANALOG OUTPUT MODULES</b>		
Number of channels	1 or 4, separately isolated channels	
Resolution	65,000 units, 16 bits	
Voltage output	0 to 10 V, –10 to 10 V, >1 kΩ load	
Current output	4 to 20 mA, 0 to 20 mA, –12 to 20 mA or –20 to 20 mA <500 Ω load	
Update rate	Analog input update rate, adjustable smoothing filter	

## Advanced Process Control Instruments Family

### ORDERING INFORMATION

Part Number Nomenclature: G4-PM-FB-S1-S2-S3-S4-S5-S6-P

Code	Type	Part Number Reference	Description
<b>G4</b>	Instrument type	G4	—
<b>PM</b>	Enclosure type	PM HE	Panel mount Harsh environment
<b>FB</b>	Fieldbus interface	0 P D	None Profibus DeviceNet
<b>Si</b>	Slot 1 to 6 type	0 2 3 4 6 7 8	Blank HSWF2—High speed weight/force, dual input module WFIN1—Weight/force, single input module WFIN2—Weight / force, dual input module AOUT1—Analog output, single channel AOUT4—Analog output, 4 channels DIO8—Digital input and output module
<b>P</b>	Power supply	D A	DC power supply AC power supply
<b>S</b>	Software version	W F S	Weighing Force Special version (contact factory for option code)

**Example of actual part number: G4-PM-0-4-8-0-0-0-0-D-F**

Where:

G4 instrument (G4)

Panel mount (PM)

No field bus (0)

Slot 1 = WF1 (4)

Slot 2 = DIO8 (8)

Slot 3 = Blank (0)

Slot 4 = Blank (0)

Slot 5 = Blank (0)

Slot 6 = Blank (0)

Power = DC supply (D)

Software = Force

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at [vpgsensors.com](http://vpgsensors.com).

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.

Document No.: 63999 Revision: 15-Jul-2014