

# Safety Data Sheet



according to OSHA Hazard Communication  
29 CFR Part 1910.1200

## Section 1. Identification

**Product Information:** 25W-G030

**Product Name:** WHITE 98:2 AREA MARKING

**Recommended Use:** Liquid Paint

**Application Method:** Liquid Surface Paint

**Supplied by:** Aexcel Corporation  
7373 Production Drive.  
Mentor, OH 44060

**Emergency Telephone:** Chemtrec: 800-424-9300

**Safety Data Sheet Coordinator:** IWebb@AexcelCorp.com

## Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** Flammable liquid and vapor.

### GHS Classification

Flam. Liq. 1, STOT SE 3 RTI, Skin Irrit. 2, Skin Sens. 1

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.

### GHS LABEL PRECAUTIONARY STATEMENTS

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).

P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local rules and regulations.

**GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

**Section 3. Composition/Information on ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
METHYL METHACRYLATE	80-62-6	10-25	GHS02-GHS07	H225-315-317-335
N-BUTYL ACRYLATE	141-32-2	10-25	GHS02-GHS07	H226-315-317-319-332-335

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**Section 4. First-aid measures**

**FIRST AID - INHALATION:** Move to fresh air.

**FIRST AID - SKIN CONTACT:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

**FIRST AID - EYE CONTACT:** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

**FIRST AID - INGESTION:** Call a physician immediately. Do not induce vomiting without medical advice.

**Section 5. Fire-fighting measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**Section 6. Accidental release measures**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

**Section 7. Handling and storage**

**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up.

**Section 8. Exposure controls/personal protection****Ingredients with Occupational Exposure Limits**

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
N-BUTYL ACRYLATE	2 ppm	NE	10 ppm	NE

METHYL METHACRYLATE                      50 ppm                      100 ppm                      100 ppm                      NE

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



**SKIN PROTECTION:** Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited.

## 9. Physical and Chemical Properties

<b>Boiling Range:</b>	0 - 0	<b>Vapor Density:</b>	3.60
<b>Odor:</b>	Characteristic	<b>Odor Threshold:</b>	NE
<b>Appearance:</b>	Heavy White Liquid	<b>Evaporation Rate:</b>	3.10
<b>Solubility in Water:</b>	NE	<b>Specific Gravity:</b>	1.646
<b>Freeze Point:</b>	NE	<b>pH:</b>	NE
<b>Vapor Pressure:</b>	40.00	<b>Viscosity:</b>	NE
<b>Physical State:</b>	Liquid	<b>Flash Point, °C:</b>	10, °F 50

(See section 16 for abbreviation legend)

<u>CHEMICAL NAME</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>BOILING POINT</u>	<u>VP mmHg</u>	<u>at DEG. F</u>
METHYL METHACRYLATE	3.60	3.1	212	40	68
N-BUTYL ACRYLATE	0.899	NA	298	4.3	68

## Section 10. Stability and reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing.

**INCOMPATIBILITY:** Strong oxidizing agents. Keep away from strong oxidizing agents, heat and open flames.

**HAZARDOUS DECOMPOSITION PRODUCTS:** No decomposition if stored and applied as directed.

## Section 11. Toxicological information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful: may cause lung damage if swallowed.

**CARCINOGENICITY:** No Information

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
141-32-2	N-BUTYL ACRYLATE	N.I.	N.I.	N.I.
80-62-6	METHYL METHACRYLATE	N.I.	N.I.	N.I.

N.I. - No Information

### Section 12. Ecological information

**ECOLOGICAL INFORMATION:** Do not contaminate ponds, waterways or ditches with chemical or used container.

### Section 13. Disposal considerations



Product

**DISPOSAL METHOD:** Contact waste disposal services.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

### Section 14. Transport information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

DOT Proper Shipping	Paint, Flammable Liquid	Packing Group:	II
DOT Technical Name:	Paint	Hazard SubClass:	No Information
DOT Hazard Class:	3	Resp. Guide Page:	128
DOT UN/NA Number:	1263		

### Section 15. Regulatory information

#### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard

#### SARA SECTION 312:

<u>Chemical Name</u>	<u>CAS-No.</u>
METHYL METHACRYLATE	80-62-6
N-BUTYL ACRYLATE	141-32-2

**SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
N-BUTYL ACRYLATE	141-32-2
METHYL METHACRYLATE	80-62-6
XYLENE (100%)	1330-20-7
ETHYL BENZENE	100-41-4

**TOXIC SUBSTANCES CONTROL ACT:**

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
LIMESTONE	1317-65-3
TITANIUM DIOXIDE	13463-67-7

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
LIMESTONE	1317-65-3
TITANIUM DIOXIDE	13463-67-7
BUTYL METHACRYLATE COPOLYMER	28262-63-7

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
ETHYL BENZENE	100-41-4

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

**International Regulations: As follows -****CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

**WHMIS Class:** No Information

## Section 16. Other information, including date of preparation of the last revision

**Revision Date:** 11/13/2015 **Supersedes Date:** New MSDS  
**Reason for revision:** GHS  
**Datasheet produced by:** Regulatory Department

### HMIS Ratings:

<b>Health:</b>	2	<b>Flammability:</b>	3	<b>Reactivity:</b>	2	<b>Personal Protection:</b>	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

**Volatile Organic Compounds, gr/ltr:** 7

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.  
 H226 Flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H335 May cause respiratory irritation.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02



GHS07



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information