# Safety Data Sheet



## according to OSHA Hazard Communication 29 CFR Part 1910.1200

# Section 1. Identification

25Y-G030
YELLOW 98:2 MMA PROFILE
Liquid Paint
See Product Data Sheet
Aexcel Corporation 7373 Production Drive. Mentor, OH 44060
Chemtrec: 800-424-9300 IWebb@AexcelCorp.com

## Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

### **GHS Classification**

Flam. Liq. 1, Skin Irrit. 2, Skin Sens. 1

## Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

20% of the mixture consists of ingredients of unknown acute toxicity

## GHS HAZARD STATEMENTS

Flammable Liquid, category 1	H224	Extremely flammable liquid and vapour.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
GHS LABEL PRECAUTIONARY ST	ATEMENTS	
P210	Keep awa	ay from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.	
P233	Keep con	tainer tightly closed.
P261	Avoid bre	athing dust/fume/gas/mist/vapours/spray.
P264	Wash tho	roughly after handling.
P272	Contamin	ated work clothing should not be allowed out of the workplace.
P280	Wear pro	tective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SK	IN: Wash with plenty of water.
P303+P361+P353	IF ON SK water/sho	IN (or hair): Take off immediately all contaminated clothing. Rinse skin with wer.

P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P370+P378	In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local rules and regulations.
GHS SDS PRECAUTIONARY STATEM	ENTS
P240	Ground/bond container and receiving equipment.
P240 P241	Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.
	5 1 1
P241	Use explosion-proof electrical/ventilating/lighting/equipment.

## Section 3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
METHYL METHACRYLATE	80-62-6	10-25	GHS02-GHS07	H225-315-317-335
2-ETHYLHEXYL ACRYLATE	103-11-7	2.5-10	GHS07	H315-317-335
TITANIUM DIOXIDE	13463-67-7	1.0-2.5	GHS06-GHS08	H331-361

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

**FIRST AID - EYE CONTACT:** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

FIRST AID - INGESTION: Call a physician immediately. Do not induce vomiting without medical advice.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

## Section 6. Accidental release measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7. Handling and storage



**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice. Keep out of reach of children.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

## Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits						
<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING		
METHYL METHACRYLATE	50	100	100	NE		
2-ETHYLHEXYL ACRYLATE	3 mg/m3	NE	NE	NE		
TITANIUM DIOXIDE	N.E.	N.E.	N.E.	N.E.		

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### **Personal Protection**



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.

HYGIENIC PRACTICES: General industrial hygiene practice. Remove and wash contaminated clothing before re-use.

## Section 9. Physical and Chemical Properties

Boiling Range: Odor: Appearance: Solubility in Water: Freeze Point: Vapor Pressure: Physical State:	0 - 0 Characteristic Heavy Yellow Lic NE No Information 40.00 Liquid	quid	Vapor D Odor Th Evapora Specific pH: Viscosity Flash Po	reshold: tion Rate: Gravity: y:	3.1 1.9 NE NE	Information 0 34	
(See section 16 for abbrevi	ation legend)						
CHEMICAL NAME	VAPOR DENSITY	EVAPORATION	N RATE	BOILING POIN	IT	<u>VP mmHg</u>	<u>at DEG. F</u>
METHYL METHACRYLAT	E3.60	3.10		212		40.00	68
2-ETHYLHEXYL ACRYLATE	6.40	NA		419		0.20	68
TITANIUM DIOXIDE	NE	NE		0		NE	NE

## Section 10. Stability and reactivity

STABILITY: Stable under normal conditions. Stable if used as directed.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing.

INCOMPATIBILITY: Strong oxidizing agents. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed.

## Section 11. Toxicological information



**Practical Experiences** 

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed. Harmful if swallowed.

**CARCINOGENICITY: No Information** 

#### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	<u>Oral LD50</u>	Dermal LD50	Vapor LC50
80-62-6	METHYL METHACRYLATE	N.I.	N.I.	N.I.
103-11-7	2-ETHYLHEXYL ACRYLATE	N.I.	N.I.	N.I.
13463-67-7	TITANIUM DIOXIDE	10000	10000	6.80

N.I. - No Information

## Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

## Section 13. Disposal considerations



Product

DISPOSAL METHOD: Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 14. Transport information

## SPECIAL TRANSPORT PRECAUTIONS: No Information

3

**DOT Proper Shipping** DOT Technical Name: **DOT Hazard Class:** DOT UN/NA Number:

Paint, Flammable Liquid Paint 1263

Packing Group: Hazard SubClass: Resp. Guide Page: Ш No Information 128

## Section 15. Regulatory information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization

#### SARA SECTION 312:

Chemical Name	CAS-No.
METHYL METHACRYLATE	80-62-6
2-ETHYLHEXYL ACRYLATE	103-11-7

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
METHYL METHACRYLATE	80-62-6
1-METHYL-2-PYRROLIDONE	872-50-4
XYLENE (100%)	1330-20-7
ETHYL BENZENE	100-41-4

### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

## U.S. State Regulations:

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
LIMESTONE	1317-65-3
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE

#### **PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
LIMESTONE	1317-65-3
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE
YELLOW 65	6528-34-3

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

WARNING

The following ingredients present in the product are known to the state of California to cause Cancer:

#### **Chemical Name**

#### CAS-No.

TITANIUM DIOXIDE	13463-67-7
N,N-DIMETHYL-P-TOLUIDINE	99-97-8
ETHYL BENZENE	100-41-4

## **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

#### **Chemical Name**

Chemical Name	CAS-No.
1-METHYL-2-PYRROLIDONE	872-50-4

## International Regulations: As follows -

#### **CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

## Section 16. Other information, including date of preparation of the last revision

<b>Revision Date:</b> 4/23/2021				Supercedes Date			8/16/2019
Reason for revision:Revision Description Changed Product Composition Changed Substance and/or Product Proper 01 - Product Information 05 - Flammability Information 09 - Physical & Chemical Information 15 - Regulatory Information 16 - Other Information Revision Statement(s) Changed			nged t Properties Chang tion Information on	ged in Sectio	on(s):		
Datasheet	atasheet produced by: Regulatory Department						
HMIS Rati	ngs:						
Health:	3	Flammability:	3	Reactivity:	2	Personal Protection:	Х

8

#### Volatile Organic Compounds, gr/ltr:

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.

#### Icons for GHS Pictograms shown in Section 3 describing each ingredient:





Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information