



BIO-FLOW BLOCK Reduces Odors

- SOLID, BACTERIAL LADEN, BLOCK FOR USE IN DEGRADING ORGANIC WASTE IN HIGHER FLOW SYSTEMS SUCH AS LIFT STATIONS, WET WELLS, ETC.
- REDUCES ODOR, SLUDGE, FATS, OILS AND GREASE BUILD UP.
- REDUCES HYDROGEN SULFIDE AND SLUDGE BUILDUP AND BREAKS DOWN ODORS, FECAL MATTER, AND GREASE COMPOUNDS.

KEEP OUT OF REACH OF CHILDREN

See side panel for additional safety information.

NET CONTENTS:

□ 4 x 2lbs □ 4 x 5lbs □ 1 x 30lbs

distributed by:

Chemex Industries Inc.

#3 Chattanooga

Irvine, CA 92620-2514

Phone: 714-832-8441

barry@chemexindustries.com

WARNING

Causes skin irritation.
Causes serious eye irritation.



Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention.

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.

DIRECTIONS

New Blocks will dissolve gradually over a 45-90 day period (depending upon flow rate) allowing for continuous treatment of waste.

Easy to use: Remove Block from box. Suspend Block from a rope into treatment area. Change out the spent block every 45-90 days.

NFPA® RATINGS

Health: 1; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Bacillus Genus/No CAS Number

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*



Please Recycle.

0522.060815