



CL-2 is designed as a corrosion inhibitor for either chilled or hot water closed loop systems.

CL-2 is a liquid blend of three major corrosion inhibitors, a surfactant and an iron oxide reducing agent.

FIELD CONTROL:

Control nitrite levels between 800 and 1,000 ppm.

READ ALL CAUTIONS AND MATERIAL SAFETY DATA SHEETS BEFORE OPENING CONTAINER

PRECAUTIONARY STATEMENTS HAZARDS

DANGER: Contact may cause burns to skin and eyes... Do not get in eyes, on skin or on clothing. Avoid breathing vapor or mist. Keep away from heat or open flame. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling.

CL-2

CLOSED LOOP TREATMENT

KEEP OUT OF REACH OF CHILDREN

5 GALLONS 18.92 LTR

CHEMEX INDUSTRIES, INC.

3 Chattanooga

Irvine, CA 92620

Phone: 714-832-8441

FIRST AID: IN CASE OF CONTACT: EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Hold eyelids open while washing. Immediately see a physician. **SKIN:** Immediately flush skin with plenty of water, while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean or discard contaminated shoes. Call a physician if irritation occurs. **Ingestion:** Do NOT induce vomiting. Drink a quart of water. Never give liquids to an unconscious person. Immediately see a physician.

PROTECTIVE EQUIPMENT: Wear and use suitable protective equipment. Vapor proof goggles, impervious gloves, protective long-sleeved clothing (impervious apron) should be worn and laundered before reuse. Have eye wash and safety shower available.

DIRECTIONS: USE IN ACCORDANCE WITH INSTRUCTIONS PER CHEMEX INDUSTRIES, INC.

Health	2
Flammability	0
Reactivity	2
Protection	C