

DESCRIPTION

FIREBALL H&G is a true breakthrough in drain opener technology. With a pH of 13 and caustic formulation, this fast-acting product offers the performance of traditional caustic drain openers, but is biodegradable, non-irritating to skin, and ships DOT non-hazardous.

Its high density, thickened formula is heavier than water, so it sinks and clings to the blockage and begins working quickly. Highly effective against obstructions caused by fats, oils, lint and hair. Odorless, nonflammable, and safer to use than traditional drain openers.

Wash thoroughly after handling. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

DISPOSAL

Offer empty container for recycling. If recycling is not available, discard container in trash.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

distributed by:

Chemex Industries Inc.

#3 Chattanooga

Irvine, CA 92620-2514

Phone: 714-832-8441

barry@chemexindustries.com

FIREBALL H&G



SAFER-CAUSTIC DRAIN OPENER

- pH OF 13, BUT NON-IRRITATING TO SKIN
- THICKENED FORMULA SINKS & CLINGS TO POINT OF OBSTRUCTION
- HIGHLY EFFECTIVE AGAINST FATS, OILS, LINT & HAIR
- ODORLESS, BIODEGRADABLE, NONFLAMMABLE
- SHIPS DOT NON-HAZARDOUS

WARNING

Causes eye irritation.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ONE QUART (32 fl. oz.)

DIRECTIONS

Ensure cap is secured and invert container prior to use.

FOR SEWER MAINS:

Pour 2-4 gallons of **FIREBALL H&G** into manhole or drain upstream and as close to the obstruction as possible. For best results, use regularly to keep sewer main open and free flowing.

FOR LATERALS:

Pour 1 gallon into drain upstream and as close to the obstruction as possible.

FOR DRAINS:

Pour 1/2-1 quart slowly into the drain. Allow to work for 30 minutes. For difficult obstructions, a second application may be necessary.

Where there is a history of obstructions, the regular use of this product at weekly intervals (or more often if required) will keep the line open and free flowing.

NFPA® RATINGS

Health: 0; Flammability: 0; Reactivity: 0

CONTAINS/CAS NUMBER:

Water/7732-18-5;

Trade Secret/Proprietary;

Xanthan Gum/11138-66-2;

Alcohol Ethoxylate/68439-46-3;

Modified Magnesium Silicate/53320-86-8.



Please Recycle.