

Multi-Purpose Continuous Coating Instant Leak Sealer

RAPID SEAL can be applied to any surface to provide a waterproof flexible continuous rubber coating that will stop leaks and act as a barrier against moisture, rust, and corrosion. Once applied, area becomes impervious to humidity, mold, and fungus. RAPID SEAL is fast drying and will not crack or peel.

DIRECTIONS: Shake can well until ball rattles & then for a further 30 seconds. For best results use & store at room temperature. Remove dust from area before application. Apply to surface from a distance of 10-12 inches. Spray evenly over desired area. Multiple coats can be applied, but allow approximately 20-30 minutes of drying time between coats. Leaks, breaks & large cracks may be repaired by coating around defect & applying a mesh such as a heavy cloth, wire mesh or fiberglass before final coating is applied. Clean actuator tip after use by inverting can and spraying until only gas comes out.

WARNING: Static Electricity may cause flash fires!

CAUTIONS: Contents under pressure. Use only as directed. EXTREMELY FLAMMABLE. Do not apply to energized equipment. Do not use near open flames, sparks, electric arcs. Do not puncture, compact or incinerate. Do not expose to temperatures above 120°F. Exposure to heat may cause bursting. Use only in well ventilated areas. Intentional misuse may be harmful or fatal.

MIR: NFP 1.4

CONTAINS: Xylene (1330-20-7), Aromatic Hydrocarbon (108-88-3), Aliphatic Hydrocarbon (110-54-3), Inorganic Metal Oxide (7631-86-9), Ceramic Microspheres (66402-68-4), Methyl Acetate (79-20-9), N-Tallowalkyl Trimethylene Diamines Ole. (61791-53-5), Poly (Butadiene-Co-Styrene) (9003-55-8).

FIRST AID:

EYES: Immediately flush eyes with water for 15 minutes and seek physician promptly.

SKIN: Wash with soap and warm water. Contact physician if irritation develops.

INHALATION: Vapors may cause respiratory irritation. Move to well ventilated area.

INGESTION: If swallowed, consult physician immediately. DO NOT induce vomiting unless directed by qualified medical personnel.

WARNING: In accordance with Prop. 65, This product contains a chemical(s) known to the State of California to cause cancer, birth defects and other reproductive harm. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN

CHEMEX INDUSTRIES, Inc.

PH: (714) 832-8441

www.chemexindustries.com



MADE IN THE U.S.A.



RAPID SEAL BLACK

ULTRA DURABLE RUBBERIZED
CONTINUOUS COATING

INSTANTLY REPAIRS CRACKS, TEARS, SPLIT
SEAMS, THIN SPOTS, ROOF GUTTERS, AND
FLASHING DOWNSPOUTS!

Repairs, Weatherproofs & Waterproofs!
Each Can Covers up to 20 SQ. FT.

DANGER!

Extremely Flammable

Liquid & Vapors may Cause Flash Fire.
Contents Under Pressure. Vapor Harmful.
Harmful or Fatal if Swallowed.

KEEP OUT OF REACH OF CHILDREN!

Read Carefully Other Caution on Back Panel.

NET WEIGHT 16 OZ. (454 Grams)

