

DESCRIPTION

This product is a highly concentrated foam designed for use on ovens, grills, deep fryers, smokehouses, meat curers and other food processing equipment. Its powerful surfactants and caustic cleaners soften and lift tough carbon deposits, grease, fats and oils.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Immediately call a doctor, a POISON CENTER. Get medical advice/attention if you feel unwell. Absorb spillage to prevent material damage. Store locked up Store in corrosive resistant container with a resistant inner liner.

For industrial and commercial use only.
For additional information, see Safety Data Sheet.

WARNING: This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.



OVEN, GRILL & SMOKEHOUSE CLEANER

REMOVES DIRT, GREASE, FATS, OILS, CARBON AND BAKED-ON DEPOSITS

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.

Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ONE GALLON (128 FL. OZ.)

distributed by:

Chemex Industries Inc.

#3 Chattanooga
Irvine, CA 92620-2514
Phone: 714-832-8441
barry@chemexindustries.com

DIRECTIONS

- Use this foaming cleaner as is or dilute with as much as 10 parts of hot water.
- Adjust the dilution rate according to the cleaning equipment manufacturer's instructions
- Apply directly onto surface.
- Allow to penetrate and soften deposits.
- Scrape away loosened deposits.
- · Rinse with clean, hot water,

Dispose of contents/container to comply with local/regional/national/international regulations.

NFPA® Ratings

Health: 2: Flammability: 0: Reactivity: 0.

Contains/CAS Number:

Water/7732-18-5; Potassium Hydroxide/1310-58-3; 2-butoxyethanol/111-76-2; Sodium Tripolyphosphate/7758-29-4; Sodium Laureth Sulfate/9004-82-4; Sodium Metasilicate/6834-92-0; Cocoamide/8051-30-7.

