Report Number: 92012



ADHESIVE SPRAY

Our ADHESIVE SPRAY is a pressure sensitive, high solids adhesive providing either temporary or permanent bonds. It utilizes a webbing type spray pattern that is water white. ADHESIVE SPRAY does not contain Methylene Chloride. ADHESIVE SPRAY adheres to metals, laminates, fiberboard, plywood, and glass. Used by HVAC insulation, asbestos abatement, automotive, cabinetry, and signage. Used to reseal headliner, carpeting, upholstery to door panels and trunk seals

- HIGH SOLIDS
- HIGH STRENGTH
- □ FAST TACK
- n HIGH TEMPERATURE

General Purpose Pressure Sensitive Adhesive is recommended for decorative laminate to particleboard and MDF (medium density fiberboard substrates), metals and plywood. This product has an adjustable tip offering the user a webbing type spray pattern that is water white and does not contain Methylene Chloride. Its unique formula prevents soak in of the adhesive on porous surfaces. It offers the user very high coverage with a fast tack time for general purpose bonding of a wide variety of substrates.

ADHESIVE SPRAY provides both temporary and permanent tack.



H

N

I

E

P

3 Chattanooga ♦ Irvine, California ♦ 92620 ♦ Phone: 714-832-8441 e-mail: info@chemexindustries.com ♦ www.chemexindustries.com