

SOGEVAC NEO D Three times a hit.

Less noise. Less emissions. Less maintenance.



The new generation of SOGEVAC vacuum pumps. Triple-hitting for cleaner, quieter, longer-running performance.

Pairing health and safety with efficient processes is a vital need for any workplace, from research labs to industrial manufacturers. When processes rely on continuous vacuum, choosing the right components becomes all the more essential. Reliable, high-performance vacuum technology not only gets the job done, but also contributes to a better work environment with less noise and fewer emissions. The result is greater well-being and peace of mind – for higher employee productivity and precision in demanding applications.

When it comes to these universal challenges, the new SOGEVAC NEO D rotary vane vacuum pump offers a bundle of advantages. But most of all, it is cleaner, quieter and virtually maintenance-free.

Because good things come in threes



Quieter performance by design

Our designers and engineers went to great lengths to improve the acoustic properties of the rotary vane vacuum pump. And they delivered: the SOGEVAC NEO D sets a new benchmark in perceived noise levels and sound quality. It is 3 dB(A) quieter than competitors' products on average – for quality that you cannot hear.

- 54 dB(A) for SOGEVAC NEO D 16 & 25
- 57 dB(A) for SOGEVAC NEO D 40 & 65



vacuum technology



Cleaner technology

The SOGEVAC NEO D features a top-quality exhaust filter inside the oil casing. Built-in filtration reduces the required integration volume of the pump and ensures a clean environment without oil smoke or loss while pumping down. The result is far less oil loss compared to competitors' pumps without exhaust filtration – up to 100 times less! This innovative design also makes the SOGEVAC NEO D incredibly compact.



Longer running – maintenance-free for up to 3 years

Thanks to cutting-edge shaft seal technology designed exclusively for Leybold, combined with long-life hydrocarbon oils, the SOGEVAC NEO D is built for maximal uptime. The new generation of vacuum pumps permits maintenance-free operation for up to three years in clean applications. "Fit it and forget it" for a new level of performance and convenience.

The new revolution in medium vacuum – ideal for all medium vacuum applications

Reliable vacuum is indispensable to numerous applications across a variety of industries. The SOGEVAC NEO D can operate continuously at any inlet pressure and features the same sturdy industrial design as other members of the SOGEVAC series. The latest generation of SOGEVAC rotary vane vacuum pumps is suitable for all dual-stage pump applications.

Selected applications

Analytics

In analytical instruments like mass spectrometers, the vacuum pump is an essential component for reliable operation.

SOGEVAC NEO D advantages:

- Eliminates noise enclosures
- Flexible interfaces for remote control
- Pumping speeds from 16 to 80 m³/h with 180 ... 264 V; 50 & 60 Hz
 1-phase power supply
- No external exhaust filter required
- Up to 3 years of maintenance-free operation!

Glove boxes

In glove boxes, the vacuum pump is an indispensable component that provides reliable vacuum to evacuate the load lock.

SOGEVAC NEO D advantages:

- Silent, user-friendly pump
- Pumping speeds from 16 to 80 m³/h with 180 ... 264 V; 50 & 60 Hz
 1-phase power supply
- No external exhaust filter required
- Up to 3 years of maintenance-free operation!

Sterilization

In sterilization, vacuum pumps are critical components that are exposed to harsh conditions such as high quantities of water vapor, residual H_2O_2 or ethylene oxide.

SOGEVAC NEO D advantages:

- Silent, user-friendly pump
- Pumping speeds from 16 to 80 m³/h with 180 ... 264 V; 50 & 60 Hz
 1-phase power supply or a wide range of 3-phase motors
- No external exhaust filter required
- ATEX in Cat 2 or 3 variants available

R&D

Ultra-high vacuum (UHV) applications require reliable fore-vacuum generation for turbomolecular pumps. To avoid disturbing sensitive measurements, noise and vibrations must be kept to an absolute minimum.

SOGEVAC NEO D advantages:

- Extremely quiet and easy to operate
 Sufficient ultimate pressure for UHV
- performance
- No external exhaust filter required
- Up to 3 years of maintenance-free operation!
- ATEX in Cat 2 or 3 variants available

Heat treatment & plasma processes

In heat treatment furnaces and plasma processes, vacuum pump technology needs to perform reliably while exposed to difficult processes.

SOGEVAC NEO D advantages:

- Rugged industrial design with oil filter
- No external exhaust filter required
- Different oil types available depending on process!

Working pressure



SOGEVAC NEO D



Performance-boosting accessories for pump monitoring and control

Would you like to benefit from pump control options and receive access to predictive maintenance data? We offer a frequency converter (FC) driven version of the SOGEVAC NEO D in all four pump sizes.

Frequency converter drive (optional):

Black box FC drive enables

- Speed control
- Monitoring (RS485 interface)
- Constant pumping speed independent of mains frequency
- Soft start w/o inrush current
- Even lower noise and vibration levels than a 1-phase motor
- 1-phase power supply 180 ... 264 V at 50 & 60 Hz, for all pump sizes!

Pump failure indicator (optional):

Do you need to keep an eye on the status of your pump, even when you are not on site? Our pump failure indicator enables remote monitoring:

1. Oil level

Indicates a too low oil level

2. Oil temp

Indicates overheating

3. Exhaust filter condition (back-pressure) Indicates that the exhaust filter needs to be changed

Reduce your energy consumption



Power consumption of SOGEVAC NEO D 25 as a function of inlet pressure

The SOGEVAC NEO D rotary vane vacuum pump is available in four different sizes: 16, 25, 40 or 65 m³/h at 50 Hz. We also offer a variety of motors, oils and accessories, depending on your requirements.

Technical data

| Size | | 16 | | 25 | | 40 | | 65 | |
|-----------------------|-------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|
| Frequency | | 50 | 60 | 50 | 60 | 50 | 60 | 50 | 60 |
| Rated pumping speed | m³/h | 19 | 23 | 24 | 29 | 40 | 48 | 63 | 76 |
| Eff pumping speed | m³/h | 16 | 19 | 28 | 34 | 47 | 56 | 74 | 89 |
| Ult pressure w/o GB | mbar | < 8 x 10-3 | |
| Ult pressure with GB | mbar | < 1 x 10-1 | |
| Water vapor tolerance | mbar | 10 | | 10 | | 10 | | 10 | |
| Noise level | dB(A) | 54 | | 54 | | 57 | | 57 | |
| Oil volume | 1 | 1.5 | | 1.5 | | 3 | | 3 | |
| Flanges | | 25 KF | | 25 KF | | 40 KF | | 40 KF | |
| Weight | kg | 4 | 9 | 5 | 50 | 8 | 80 | 9 | 6 |
| Dimensions L x W x H | mm | 516 x | 288 x 294 | 518 x | 288 x 294 | 632 x | 356 x 320 | 669 x | 359 x 320 |

Technical data Ordering information

One model, four sizes. Find your perfect SOGEVAC NEO D...

| SOGEVAC NEO D models | | | | | | |
|---|------------------|------------------|------------------|------------------|--|--|
| Size | SOGEVAC NEO D 16 | SOGEVAC NEO D 25 | SOGEVAC NEO D 40 | SOGEVAC NEO D 65 | | |
| 3-phase world motor 180264 / 342457 V, 50 Hz & 180264 / 342506 V, 60 Hz | 970102V | 970202V | 970302V | 970402V | | |
| 3-phase ATEX Cat 2 or 3 230/400 V, 50 Hz ATEX marking | 970102A22 | 970202A22 | 970302A22 | 970402A22 | | |
| 1-phase 180 - 264V, 50 & 60 Hz with overload protection | 970100V | 970200V | 970300V | N/A | | |
| 1-phase driven F/C 180 - 264V, 50 & 60 Hz with overload protection | 970101V | 970201V | 970301V | 970401V | | |

... plus all the right accessories!

We also offer a range of accessories for enhanced monitoring and control on our pump models. All accessories can be retrofitted on any pump and are designed according to the same basic principles of the SOGEVAC series. SOGEVAC NEO D pumps are also compatible with TRIVAC B inlet accessories.

| SOGEVAC NEO D accessories Pump monitoring and control | | | | | | | |
|---|------------------|------------------|------------------|------------------|--|--|--|
| Size | SOGEVAC NEO D 16 | SOGEVAC NEO D 25 | SOGEVAC NEO D 40 | SOGEVAC NEO D 65 | | | |
| Oil level switch | 9700LS | 9700LS | 9700LS | 9700LS | | | |
| Exhaust filter over-pressure switch | 971471210 | 971471210 | 971471210 | 971471210 | | | |
| Exhaust filter pressure manometer | 95193 | 95193 | 95193 | 95193 | | | |
| Temperature switch | 9700TS | 9700TS | 9700TS | 9700TS | | | |
| PT100 | N/A | N/A | 971444320 | 971444320 | | | |

Leybold

Leybold GmbH Bonner Str. 498 · D-50968 Köln T +49 (0) 221-347-0 F +49 (0) 221-347-1250 info@leybold.com

www.leybold.com www.leybold-sogevac-neo-d.com



