





Cyklop CLT 120 - so light and so strong

Competitively priced - it is an ideal introduction to battery-powered strapping.

Simple and fast

- Automatic or semi-automatic tensioning, sealing and strap cut-off per one push button.
- Application-selectable modes of operation: Automatic, semi-automatic, manual and soft

Reliable

- ➤ High quality
- ➤ Constant strapping
- ➤ Faulty operation avoidance (automatic)
- ➤ Soft mode:
 - For strapping with PP strap
 - For the strapping of fragile goods

Economic

- Energy efficient strapping system
- More strapping per battery load
- ➤ Low upkeep
- ➤ Service-friendly construction

Environmentally-friendly

- ➤ Latest technology with battery from Bosch
- ➤ High efficiency factor
- ➤ No memory effect
- Battery rechargeable at any time
- ➤ Long life

Technical data

Weight:

Dimensions (LxWxH): Tension: - Soft: Tensioning speed: Seal: 3.4 kg (incl. battery) 320 x 138 x 148 mm (0) 400 - 1,200N (0) 150 - 750 N 220 mm/s Friction seal

Strapping

Material: Strap width:

Voltage:

Strap width: Strap thickness: Polypropylene (PP) / Polyester (PET)

PP/PET: 9 - 13 mm 0.4 - 0.8 mm

Rechargeable Battery

Li-Ion-battery (Bosch):

Loading time:

No. of strapping cycles per load:

14.4 V / 1.3 Ah

Approx. 20 up to 45 min.*

200 – 400 **

115/230 V

Options

- Steel plate to protect the surface against wear
- Suspension bow
- Touch panel protection

WWW.CYKLOP.COM DIRECT LINE: +49 (0) 2236 602 0

CYKLOP GmbH Industriestraße 133 50996 Cologne Germany info@cyklop.de





^{*} after 20 min. approx 75% load capacity

^{**} depending on strap quality, strap tension and package