



WRAPPING TECHNOLOGY

AUTOMATIC PALLET WRAPPER CSM 201 / 212



Automatic Pallet Wrapper CSM 201 / 212 / Advanced

CSM 201 / 212 / Advanced are automatic pallet wrapping machines for wrapping loads of variable forms and weights with stretch or perforated stretch film.

Advantages:

- Wrapping loosely stacked pallet loads with stretch film
- Adaptation to diverse pallets sizes and loads per adjustable wrapping programmes
- Variably adjustable parameters per control panel
- Easy operation
- Up to 200 pallets per load
- For standard film and stretch film
- Safety stop by motor brakes
- CE – label

Equipment:

- Sealed and maintenance-free double battery
- Package height detection per photo-cell
- Signal light and beeper
- Stretch system lifting and lowering speeds are adjustable per frequency converter
- Mechanical fall protection for the stretch system

Adjustable Parameter per Operating Panel:

- Top and bottom wraps (1 to 10 each)
- Wrapper cycle speed (0.2 up to 93 m/min.)
- Stretch system lifting and lowering speeds (0 up to 3.4 m/min)
- Photo-cell switching delay



CSM operator panel

Options Stretch Wrapper CSM:

- Manual roping device – forming the film to a solid cord for additional package stability
- Mast extension for max. package height 2,800 mm
- Photo-cell for black and high gloss packages
- Film consumption visible by operator panel (only available for CSM 212 Advanced)

Wrapping Programme:

- Normal wrapping (upwards and downwards)
- Economical wrapping (upwards or downwards)
- Rainproof (wrapping programme for placing the top sheet manually)
- Individual task per push button
- Wrapping programme for extra large packages

Technical Data:

- Machine weight: approx. 325 kg
- Min. package dimensions: 600 x 600 mm
- Max. package height (incl. pallet): 2,100 mm
- Integrated fast charging device: 1Ph/N/PE, 230 V, 50/60 Hz
- Charging time: 8 - 10 h
- Operating temperatur: +5 °C to +40 °C

CSM 201:

Stretch System: FM

- Equipped with a film stretching system, type FM, this ranges up to 120%. This system can be adjusted quickly and simply per hand wheel.

CSM 212:

Stretch System: PRS

- Equipped with a film pre-stretch system, type PRS with pre-stretch from 150% up to 250%. The pre-stretch can be changed quickly and easily by exchanging gear wheel pairs.

CSM 212 Advanced:

Stretch System: PRS

- Equipped with a film pre-stretch system, type PRS with pre-stretch from 150% up to 250%. The pre-stretch can be changed quickly and easily by exchanging gear wheel pairs
- 99 free programmable wrapping programmes.

WWW.CYKLOP.COM

DIRECT CONTACT: +49 (0) 2236 602 0

CYKLOP GmbH
Industriestraße 133
50996 Cologne
Germany
info@cyklop.de

