

**PET350X**

# FILM DATA SHEET



159 Crocker Park Blvd, 4th Floor  
Westlake, Ohio 44145  
Toll Free: 866-440-2123  
By Fax: 216-591-1276  
Email: [info@standuppouches.net](mailto:info@standuppouches.net)  
Web: [www.standuppouches.net](http://www.standuppouches.net)

Exterior  
52 gauge PVDC coated PET  
3 mil LLDPE  
Interior

## Physical Description:

3.5mil Clear PVDC PET/Poly laminated barrier film

## Application:

This laminated material is transparent and can be used for a wide variety of packaging applications ranging from machine parts to food applications where a clear barrier material is required. This film is FDA approved and has high contact clarity. It is used extensively in food and medical industries where very good MVTR and OTR is required. Common applications include nuts, dried fruit, granola,

## Converting:

It can be converted in many ways: 2-seal pouch, 3-seal pouch, side gusset, stand up pouch and tubing. Features include: recloseable zipper, tear notch, round hang hole, and sombrero hang hole. The PET350X can also be surface printed or reverse-trapped printed. It is available in web widths to 60"

## Physical Properties:

PROPERTIES	TEST METHOD	UNIT OF MEASURE	TYPICAL VALUE
Caliper		mils	3.5
Yield		sq.in/Lb	8180
MVTR	Mocon	gms/100 sq. in./24 hrs	0.1
OTR	ASTM-1434-66	cc/100 sq. in./24 hrs	0.3

The values indicated in this document are the results of tests made in compliance with the normal standards. They are given as an indication and should be considered as average values and given without any obligation on our part. This information was provided directly to us by our film supplier.

For more information about material data, please visit our web site at [www.standuppouches.net](http://www.standuppouches.net).